



**VARIOUS ELECTRICAL-AND-THERMOELECTRIC LAWS,
RELATIONS, AND COEFFICIENTS IN NEW n(p)-TYPE
DEGENERATE “COMPENSATED” CdTe(1-x)S(x) [Y(x) $\equiv$ CdTe(1-x)
Se(x)]-CRYSTALLINE ALLOYS, ENHANCED BY OUR STATIC
DIELECTRIC CONSTANT LAW, ACCURATE FERMI ENERGY, AND
ELECTRICAL CONDUCTIVITY MODEL (XIX)**

Prof. Dr. Huynh Van Cong*, Prof. Dr. Paul Blaise and Michel Cayrol

Université de Perpignan Via Domitia, Laboratoire de Mathématiques et Physique (LAMPS),
EA 4217, Département de Physique, 52, Avenue Paul Alduy, F-66 860 Perpignan, France.

Article Received on 12/04/2025

Article Revised on 02/05/2025

Article Accepted on 22/05/2025



*Corresponding Author

**Prof. Dr. Huynh Van
Cong**

Université de Perpignan Via
Domitia, Laboratoire de
Mathématiques et Physique
(LAMPS), EA 4217,
Département de Physique,
52, Avenue Paul Alduy, F-
66 860 Perpignan, France.

ABSTRACT

In $n^+(p^+) - p(n)$ X(x) $\equiv$ CdTe(1-x)S(x) [Y(x) $\equiv$ CdTe(1-x)Se(x)]-crystalline alloys, $0 \leq x \leq 1$, taking into account their different values of energy-band-structure parameters, as given in Table 1, and also basing on the same physical model and mathematical treatment method, as used in our recent works^[1, 2, 3], various electrical-and-thermoelectric laws, relations, and coefficients, enhanced by our static dielectric constant law given in Equations (1a, 1b), which is due to the effects of the size of donor (acceptor) d(a)-radius $r_{d(a)}$ and the x-concentration, by our accurate Fermi energy, as given in Eq. (11), and finally by our electrical conductivity model, as given in Eq. (14), are now investigated. One notes that, for $x=0$, their obtained numerical

results are reduced to those obtained in the n(p)-type degenerate **CdTe-crystal**, in which all the numerical results, obtained in the same physical conditions, are found to be equal, as those observed in Tables 3n(p), 4n(p), 5n(p) and 6n(p), given in Appendix 1. So, some remarkable results can be cited as follows. In Tables 5n(5p), for a given impurity-density **N** and with increasing temperature T, and then in Tables 6n(6p), for a given **T** and with

decreasing N , the reduced Fermi-energy $\xi_{n(p)}$ decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows by: (increase: $\nearrow$, decrease: $\searrow$). Furthermore, one notes in these Tables that, for any given x , $r_{d(a)}$ and N (or T), with increasing T (or decreasing N) one obtains: (i) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, while the numerical results of the Seebeck coefficient S present a same minimum $(S)_{\min.} (\simeq -1.563 \times 10^{-4} \frac{V}{K})$, those of the figure of merit ZT show a same maximum $(ZT)_{\max.} = 1$, (ii) for $\xi_{n(p)} = 1$, the numerical results of S , ZT , the Mott figure of merit $(ZT)_{\text{Mott}}$, the first Van-Cong coefficient $VC1$, and the Thomson coefficient Ts , present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715 , 3.290 , $1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$, respectively, and finally (iii) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, $(ZT)_{\text{Mott}} = 1$. It seems that these same obtained results could represent a new law in the thermoelectric properties, obtained in the degenerate case ($\xi_{n(p)} \geq 0$).

KEYWORDS: Electrical conductivity, Seebeck coefficient (S), Figure of merit (ZT), First Van-Cong coefficient ($VC1$), Second Van-Cong coefficient ($VC2$), Thomson coefficient (Ts), Peltier coefficient (Pt)

INTRODUCTION

In the $n^+(p^+) - p(n) X(x) \equiv \text{CdTe}(1-x)\text{S}(x) [Y(x) \equiv \text{CdTe}(1-x)\text{Se}(x)]$ - crystalline alloys, $0 \leq x \leq 1$, x being the concentration, the electrical-and-thermoelectric laws, relations, and various coefficients, enhanced by our static dielectric constant law, $\epsilon(r_{d(a)}, x)$, $r_{d(a)}$ being the donor (acceptor) $d(a)$ -radius, given in Equations (1a, 1b), by our accurate Fermi energy, $E_{Fn(Fp)}$, given in Eq. (11), and also by our electrical conductivity model, in Eq. (14), are now investigated, by basing on the same physical model and same mathematical treatment method, as those used in our recent works.^[1, 2, 3] It should be noted here that for $x=0$, these obtained numerical results may be reduced to those given in the $n(p)$ -type degenerate **CdTe-crystal**^[4, 5, 6-13], in which all the numerical results, obtained in the same physical conditions, are found to be equal, as those observed in Tables 3n(p), 4n(p), 5n(p) and 6n(p), given in Appendix 1. Then, some remarkable results could be noted in the following.

(1) As observed in Equations (3, 5, 6), the critical impurity density $N_{CDn(CDP)}$, defined by the generalized Mott criterium in the metal-insulator transition (MIT), is just the density of electrons (holes), localized in the exponential conduction (valence)-band tail (EBT), $N_{CDn(CDP)}^{EBT}$, being obtained with a precision of the order of $2.82 (2.88) \times 10^{-7}$, respectively, as given in our recent works [3]. Therefore, the effective electron (hole)-density can be defined as: $N^* \equiv N - N_{CDn(CDP)} \simeq N - N_{CDn(CDP)}^{EBT}$, N being the total impurity density, as that observed in the compensated crystals.

(2) The ratio of the inverse effective screening length $k_{sn(sp)}$ to Fermi wave number $k_{Fn(kp)}$ at 0 K, $R_{sn(sp)}(N^*)$, defined in Eq. (7), is valid at any N^* .

(3) The Fermi energy for any N and T , $E_{Fn(Fp)}$, determined in Eq. (11) with a precision of the order of 2.11×10^{-4} [9], affecting all the expressions of electrical-and-thermoelectric coefficients.

(4) Our expressions for the electrical conductivity, σ , and for the Seebeck coefficient, S , determined respectively in Equations (14, 19) are the basic expressions, used to determine all the electrical-and-thermoelectric coefficients.

(5) In Tables 5n(5p) given Appendix 1, for a given impurity density N and with increasing temperature T , and further in Tables 6n(6p) given Appendix 1, for a given T and with decreasing N , the reduced Fermi-energy $\xi_{n(p)}$ decreases, giving rise to the variations of various thermoelectric coefficients, as indicated by the arrows by: (increase: ↗, decrease: ↘). Furthermore, one notes in these Tables that, for any given x , $r_{d(a)}$ and N (or T), with increasing T (or decreasing N), one obtains: (i) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, while the numerical results of the Seebeck coefficient S present a same minimum $(S)_{min.} (\simeq -1.563 \times 10^{-4} \frac{V}{K})$, those of the figure of merit ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_{n(p)} = 1$, the numerical results of S , ZT , the Mott figure of merit $(ZT)_{Mott}$, the first Van-Cong coefficient $VC1$, and the Thomson coefficient Ts , present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$, respectively, and finally (iii) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, $(ZT)_{Mott} = 1$. It seems that these

same results could represent a new law in the thermoelectric properties, obtained in the degenerate case ($\xi_{n(p)} \geq 0$).

OUR STATIC DIELECTRIC CONSTANT LAW AND GENERALIZED MOTT CRITERIUM IN THE METAL-INSULATOR TRANSITION

First of all, in $\mathbf{n}^+(\mathbf{p}^+) - \mathbf{p}(\mathbf{n}) \mathbf{X}(\mathbf{x}) \equiv \text{CdTe}(1-\mathbf{x})\text{S}(\mathbf{x})$ [$\mathbf{Y}(\mathbf{x}) \equiv \text{CdTe}(1-\mathbf{x})\text{Se}(\mathbf{x})$]- crystalline alloys at $T=0$ K, we denote the donor (acceptor) d(a)-radius by $r_{d(a)}$, the corresponding intrinsic one by: $r_{do(ao)} = r_{Ge(Ge)} [r_{Si(Si)}]$, the effective averaged numbers of equivalent conduction (valence)-bands by: $g_{c(v)}$, the unperturbed relative effective electron (hole) mass in conduction (valence) bands by: $m_{c(v)}(x)/m_o$, m_o being the free electron mass, the unperturbed relative static dielectric constant by: $\epsilon_o(x)$, and the intrinsic band gap by: $E_{go}(x)$. Then, their values are reported in Table 1 in Appendix 1.

Therefore, we can define the effective donor (acceptor)-ionization energy in absolute values as:

$$E_{do(ao)}(x) = \frac{13600 \times [m_{c(v)}(x)/m_o]}{[\epsilon_o(x)]^2} \text{ meV}, \text{ and then, the isothermal bulk modulus, by :}$$

$$B_{do(ao)}(x) \equiv \frac{E_{do(ao)}(x)}{\left(\frac{4\pi}{3}\right) \times (r_{do(ao)})^3}.$$

Our Static Dielectric Constant Law

Here, the changes in all the energy-band-structure parameters, expressed in terms of the effective relative dielectric constant $\epsilon(r_{d(a)}, x)$, developed as follows.

At $r_{d(a)} = r_{do(ao)}$, the needed boundary conditions are found to be, for the impurity-atom volume $V = (4\pi/3) \times (r_{d(a)})^3$, $V_{do(ao)} = (4\pi/3) \times (r_{do(ao)})^3$, for the pressure p , $p_o = 0$, and for the deformation potential energy (or the strain energy) α , $\alpha_o = 0$. Further, the two important equations, used to determine the α -variation, $\Delta \alpha \equiv \alpha - \alpha_o = \alpha$, are defined by :

$\frac{dp}{dV} = -\frac{B}{V}$ and $p = -\frac{d\alpha}{dV}$, giving rise to : $\frac{d}{dV}\left(\frac{d\alpha}{dV}\right) = \frac{B}{V}$. Then, by an integration, one gets:

$$\left[\Delta \alpha(r_{d(a)}, x)\right]_{n(p)} = B_{do(ao)}(x) \times (V - V_{do(ao)}) \times \ln\left(\frac{V}{V_{do(ao)}}\right)$$

$$\left(\frac{V}{V_{do(ao)}}\right) = E_{do(ao)}(x) \times \left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 - 1\right] \times \ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 \geq 0.$$

Furthermore, we also showed that, as $r_{d(a)} > r_{do(ao)}$ ($r_{d(a)} < r_{do(ao)}$), the compression (dilatation) gives rise to the increase (the decrease) in the energy gap $E_{gn(gp)}(r_{d(a)}, x)$, and the effective donor (acceptor)-ionization energy $E_{d(a)}(r_{d(a)}, x)$ in absolute values, obtained in the effective Bohr model, which is represented respectively by : $\pm [\Delta\alpha(r_{d(a)}, x)]_{n(p)}$,

$$E_{gno(gpo)}(r_{d(a)}, x) - E_{go}(x) = E_{d(a)}(r_{d(a)}, x) - E_{do(ao)}(x) = E_{do(ao)}(x) \times \left[\left(\frac{\varepsilon_o(x)}{\varepsilon(r_{d(a)})} \right)^2 - 1 \right] = + [\Delta\alpha(r_{d(a)}, x)]_{n(p)},$$

for $r_{d(a)} \geq r_{do(ao)}$, and for $r_{d(a)} \leq r_{do(ao)}$,

$$E_{gno(gpo)}(r_{d(a)}, x) - E_{go}(x) = E_{d(a)}(r_{d(a)}, x) - E_{do(ao)}(x) = E_{do(ao)}(x) \times \left[\left(\frac{\varepsilon_o(x)}{\varepsilon(r_{d(a)})} \right)^2 - 1 \right] = - [\Delta\alpha(r_{d(a)}, x)]_{n(p)}.$$

Therefore, one obtains the expressions for relative dielectric constant $\varepsilon(r_{d(a)}, x)$ and energy band gap $E_{gn(gp)}(r_{d(a)}, x)$, as:

$$(i)\text{-for } r_{d(a)} \geq r_{do(ao)}, \text{ since } \varepsilon(r_{d(a)}, x) = \frac{\varepsilon_o(x)}{\sqrt{1 + \left[\left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 - 1 \right] \times \ln \left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3}} \leq \varepsilon_o(x), \text{ being a new}$$

$\varepsilon(r_{d(a)}, x)$ -law,

$$E_{gno(gpo)}(r_{d(a)}, x) - E_{go}(x) = E_{d(a)}(r_{d(a)}, x) - E_{do(ao)}(x) = E_{do(ao)}(x) \times \left[\left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 - 1 \right] \times \ln \left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 \geq 0, \quad (1a)$$

according to the increase in both $E_{gn(gp)}(r_{d(a)}, x)$ and $E_{d(a)}(r_{d(a)}, x)$, with increasing $r_{d(a)}$ and for a given x , and

$$(ii)\text{-for } r_{d(a)} \leq r_{do(ao)}, \text{ since } \varepsilon(r_{d(a)}, x) = \frac{\varepsilon_o(x)}{\sqrt{1 - \left[\left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 - 1 \right] \times \ln \left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3}} \geq \varepsilon_o(x), \text{ with a}$$

condition, given by: $\left[\left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 - 1 \right] \times \ln \left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 < 1$, being a new $\varepsilon(r_{d(a)}, x)$ -law,

$$E_{\text{gno}(\text{gpo})}(r_{d(a)}, x) - E_{\text{go}}(x) = E_{d(a)}(r_{d(a)}, x) - E_{do(ao)}(x) = -E_{do(ao)}(x) \times \left[\left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 - 1 \right] \times \ln \left(\frac{r_{d(a)}}{r_{do(ao)}} \right)^3 \leq 0, \quad (1b)$$

corresponding to the decrease in both $E_{\text{gno}(\text{gpo})}(r_{d(a)}, x)$ and $E_{d(a)}(r_{d(a)}, x)$, with decreasing $r_{d(a)}$ and for a given x .

It should be noted that, in the following, all the electrical-and-thermoelectric properties strongly depend on this **new $\varepsilon(r_{d(a)}, x)$ -law**.

Furthermore, the effective Bohr radius $a_{\text{Bn}(\text{Bp})}(r_{d(a)}, x)$ is defined by:

$$a_{\text{Bn}(\text{Bp})}(r_{d(a)}, x) \equiv \frac{\varepsilon(r_{d(a)}, x) \times \hbar^2}{m_{c(v)}(x) \times m_0 \times q^2} = 0.53 \times 10^{-8} \text{ cm} \times \frac{\varepsilon(r_{d(a)}, x)}{m_{c(v)}(x)}. \quad (2)$$

Generalized Mott Criterium in the MIT

Now, it is interesting to remark that the critical total donor (acceptor)-density in the MIT at $T=0$ K, $N_{\text{CDn}(\text{NDp})}(r_{d(a)}, x)$, was given by the Mott's criterium, with an empirical parameter, $M_{n(p)}$, as ^[2, 3]:

$$N_{\text{CDn}(\text{CDp})}(r_{d(a)}, x)^{1/3} \times a_{\text{Bn}(\text{Bp})}(r_{d(a)}, x) = M_{n(p)}, \quad M_{n(p)} = 0.25, \quad (3)$$

depending thus on our **new $\varepsilon(r_{d(a)}, x)$ -law**.

This excellent one can be explained from the definition of the reduced effective Wigner-Seitz (WS) radius $r_{\text{sn}(\text{sp}), M}$, in the Mott's criterium, being characteristic of interactions, by :

$$r_{\text{sn}(\text{sp}), M}(N, r_{d(a)}, x) \equiv \left(\frac{3}{4\pi N} \right)^{1/3} \times \frac{1}{a_{\text{Bn}(\text{Bp})}(r_{d(a)}, x)} = 1.1723 \times 10^8 \times \left(\frac{1}{N} \right)^{1/3} \times \frac{m_{c(v)}(x) \times m_0}{\varepsilon(r_{d(a)}, x)}, \quad (4)$$

being equal to, in particular, at $N = N_{\text{CDn}(\text{CDp})}(r_{d(a)}, x)$: $r_{\text{sn}(\text{sp}), M}(N_{\text{CDn}(\text{CDp})}(r_{d(a)}, x), r_{d(a)}, x) = 2.4813963$, for any $(r_{d(a)}, x)$ -values. Then, from Eq. (4), one also has :

$$N_{\text{CDn}(\text{CDp})}(r_{d(a)}, x)^{1/3} \times a_{\text{Bn}(\text{Bp})}(r_{d(a)}, x) = \left(\frac{3}{4\pi} \right)^{1/3} \times \frac{1}{2.4813963} = 0.25 = (\text{WS})_{n(p)} = M_{n(p)} \quad (5)$$

explaining thus the existence of the Mott's criterium.

Furthermore, by using $M_{n(p)} = 0.25$, according to the empirical Heisenberg parameter $\mathcal{H}_{n(p)} = 0.47137$, as those given in our previous work^[3], we have also showed that $N_{\text{CDn}(\text{CDp})}$ is just **the density of electrons (holes) localized in the exponential conduction**

(valence)-band tail , $N_{CDn(CDp)}^{EBT}$, with a precision of the order of $2.82 (2.88) \times 10^{-7}$,respectively .^[3]

It should be noted that the values of $M_{n(p)}$ and $\mathcal{H}_{n(p)}$ could be chosen so that those of $N_{CDn(CDp)}$ and $N_{CDn(CDp)}^{EBT}$ are found to be in good agreement with their experimental results. Therefore, the density of electrons (holes) given in parabolic conduction (valence) bands can be defined, as that given in compensated materials:

$$N^*(N, r_{d(a)}, x) \equiv N - N_{CDn(NDp)}(r_{d(a)}, x) = N^*, \text{ for a presentation simplicity.} \quad (6)$$

In summary, as observed in Tables 7 and 8 of our previous paper [3], one remarks that, for a given x and an increasing $r_{d(a)}$, $\varepsilon(r_{d(a)}, x)$ decreases, while $E_{gno(gpo)}(r_{d(a)}, x)$, $N_{CDn(NDp)}(r_{d(a)}, x)$ and $N_{CDn(CDp)}^{EBT}(r_{d(a)}, x)$ increase, affecting strongly all electrical-and-thermoelectric properties, as those observed in following Sections.

PHYSICAL MODEL

In $n^+(p^+) - p(n)$ $X(x)$ [$Y(x)$]- crystalline alloys, if denoting the Fermi wave number by:

$k_{Fn(Fp)}(N^*) \equiv \left(\frac{3\pi^2 N^*}{g_c(v)} \right)^{\frac{1}{3}}$, where the $g_c(v)$ -values are given in Table 1 in Appendix 1, the reduced effective Wigner-Seitz (WS) radius $r_{sn(sp)}$, characteristic of interactions, being given in Eq. (4), in which N is replaced by N^* , is now defined by:

$\gamma \times r_{sn(sp)}(N^*) \equiv \frac{k_{Fn(Fp)}^{-1}}{a_{Bn(Bp)}} < 1$, $r_{sn(sp)}(N, r_{d(a)}, x) \equiv \left(\frac{3g_c(v)}{4\pi N^*} \right)^{1/3} \times \frac{1}{a_{Bn(Bp)}(r_{d(a)}, x)}$, being proportional to $N^{*-1/3}$. Here, $\gamma = (4/9\pi)^{1/3}$, $k_{Fn(Fp)}^{-1}$ means the averaged distance between ionized donors (acceptors), and $a_{Bn(Bp)}(r_{d(a)}, x)$ is determined in Eq. (2).

Then, the ratio of the inverse effective screening length $k_{sn(sp)}$ to Fermi wave number $k_{Fn(kp)}$ at 0 K is defined by:

$$R_{sn(sp)}(N^*) \equiv \frac{k_{sn(sp)}}{k_{Fn(Fp)}} = \frac{k_{Fn(Fp)}^{-1}}{k_{sn(sp)}^{-1}} = R_{snWS(spWS)} + [R_{snTF(spTF)} - R_{snWS(spWS)}] e^{-r_{sn(sp)}} < 1, \quad (7)$$

being valid at any N^* .

Here, these ratios, $R_{snTF(spTF)}$ and $R_{snWS(spWS)}$, can be determined as follows.

First, for $N \gg N_{CDn(NDp)}(r_{d(a)}, x)$, according to the **Thomas-Fermi (TF)-approximation**, the ratio $R_{snTF(spTF)}(N^*)$ is reduced to

$$R_{snTF(spTF)}(N^*) \equiv \frac{k_{snTF(spTF)}}{k_{Fn(Fp)}} = \frac{k_{Fn(Fp)}^{-1}}{k_{snTF(spTF)}^{-1}} = \sqrt{\frac{4\gamma r_{sn(sp)}}{\pi}} \ll 1, \quad (8)$$

being proportional to $N^{*-1/6}$.

Secondly, for $N \ll N_{CDn(NDp)}(r_{d(a)})$, according to the **Wigner-Seitz (WS)-approximation**, the ratio $R_{snWS(snWS)}$ is respectively reduced to

$$R_{sn(sp)WS}(N^*) \equiv \frac{k_{sn(sp)WS}}{k_{Fn}} = 0.5 \times \left(\frac{s}{2\pi} - \gamma \frac{d[r_{sn(sp)}^2 \times E_{CE}(N^*)]}{dr_{sn(sp)}} \right), \quad (9)$$

Where $E_{CE}(N^*)$ is the majority-carrier correlation energy (CE), being determined by:

$$E_{CE}(N^*) = \frac{-0.87553}{0.0908 + r_{sn(sp)}} + \frac{\frac{0.87553}{0.0908 + r_{sn(sp)}} + \left(\frac{2[1 - \ln(2)]}{\pi^2} \right) \times \ln(r_{sn(sp)}) - 0.093288}{1 + 0.03847728 \times r_{sn(sp)}^{1.67378876}}.$$

Furthermore, in the highly degenerate case, the physical conditions are found to be given by:

$$\frac{k_{Fn(Fp)}^{-1}}{a_{Bn(Bp)}} < \frac{\eta_{n(p)}}{E_{Fno(Fpo)}} \equiv \frac{1}{A_{n(p)}} < \frac{k_{Fn(Fp)}^{-1}}{k_{sn(sp)}^{-1}} \equiv R_{sn(sp)} < 1, \quad \eta_{n(p)}(N^*) \equiv \frac{\sqrt{2\pi \times \left(\frac{N^*}{E_c(v)} \right)}}{s(r_{d(a)})} \times q^2 k_{sn(sp)}^{-1/2}, \quad (10)$$

$$\text{Which gives: } A_{n(p)}(N^*) = \frac{E_{Fno(Fpo)}(N^*)}{\eta_{n(p)}(N^*)}, \quad E_{Fno(Fpo)}(N^*) \equiv \frac{\hbar^2 \times k_{Fn(Fp)}^2(N^*)}{2 \times m_{c(v)}(x) \times m_0}.$$

FERMI ENERGY AND FERMI-DIRAC DISTRIBUTION FUNCTION

Fermi Energy

Here, for a presentation simplicity, we change all the sign of various parameters, given in the $p^+ - X(x)$ - crystalline alloy in order to obtain the same one, as given in the $n^+ - X(x)$ - crystalline alloy, according to the reduced Fermi energy $E_{Fn(Fp)}$, $\xi_{n(p)}(N, r_{d(a)}, x, T) \equiv \frac{E_{Fn(Fp)}(N, r_{d(a)}, x, T)}{k_B T} > 0 (< 0)$, obtained respectively in the degenerate (non-degenerate) case.

For any $(N, r_{d(a)}, x, T)$, the reduced Fermi energy $\xi_{n(p)}(N, r_{d(a)}, x, T)$ or the Fermi energy $E_{Fn(Fp)}(N, r_{d(a)}, x, T)$, obtained in our previous paper^[9], obtained with a precision of the order of 2.11×10^{-4} , is found to be given by:

$$\xi_{n(p)}(u) \equiv \frac{E_{Fn(Fp)}(u)}{k_B T} = \frac{G(u) + Au^B F(u)}{1 + Au^B} \equiv \frac{V(u)}{W(u)}, \quad A = 0.0005372 \text{ and } B = 4.82842262, \quad (11)$$

where u is the reduced electron density, $u(N, r_{d(a)}, x, T) \equiv \frac{N^*}{N_{c(v)}(T, x)}$,
 $N_{c(v)}(T, x) = 2g_{c(v)} \times \left(\frac{m_{c(v)}(x) \times m_0 \times k_B T}{2\pi \hbar^2} \right)^{\frac{3}{2}} \text{ (cm}^{-3}\text{)}$, $F(u) = au^{\frac{2}{3}} \left(1 + bu^{-\frac{4}{3}} + cu^{-\frac{8}{3}} \right)^{-\frac{2}{3}}$,
 $a = [3\sqrt{\pi}/4]^{2/3}$, $b = \frac{1}{8} \left(\frac{\pi}{a} \right)^2$, $c = \frac{62.3739855}{1920} \left(\frac{\pi}{a} \right)^4$, and $G(u) \simeq \text{Ln}(u) + 2^{-\frac{3}{2}} \times u \times e^{-du}$,
 $d = 2^{3/2} \left[\frac{1}{\sqrt{27}} - \frac{3}{16} \right] > 0$.

So, in the non-degenerate case ($u \ll 1$), one has: $E_{Fn(Fp)}(u) = k_B T \times G(u) \simeq k_B T \times \text{Ln}(u)$
as $u \rightarrow 0$, the limiting non-degenerate condition, and in the very degenerate case ($u \gg 1$),
one gets: $E_{Fn(Fp)}(u \gg 1) = k_B T \times F(u) = k_B T \times au^{\frac{2}{3}} \left(1 + bu^{-\frac{4}{3}} + cu^{-\frac{8}{3}} \right)^{-\frac{2}{3}} \simeq \frac{\hbar^2 \times k_{Fn(Fp)}^2(N^*)}{2 \times m_{c(v)}(x) \times m_0}$
as $u \rightarrow \infty$, the limiting degenerate condition. In other words, $\xi_{n(p)} \equiv \frac{E_{Fn(Fp)}}{k_B T}$ is accurate,
and it also verifies the correct limiting conditions.

In particular, at $T=0K$, since $u^{-1} = 0$, Eq. (11) is reduced to: $E_{Fno(Fpo)}(N^*) \equiv \frac{\hbar^2 \times k_{Fn(Fp)}^2(N^*)}{2 \times m_{c(v)}(x) \times m_0}$,
being proportional to $(N^*)^{2/3}$, and also equal to 0 at $N^* = 0$, according to the MIT.

In the following, it should be noted that all the electrical-and-thermoelectric properties strongly depend on such the accurate expression of $\xi_{n(p)}(N, r_{d(a)}, x, T)$.^[9]

Fermi-Dirac Distribution Function (FDDF)

The Fermi-Dirac distribution function (FDDF) is given by: $f(E) \equiv (1 + e^\gamma)^{-1}$,
 $\gamma \equiv (E - E_{Fn(Fp)})/(k_B T)$.

So, the average of E^p , calculated using the FDDF-method, as developed in our previous works [1, 6] is found to be given by:

$$\langle E^p \rangle_{FDDF} \equiv G_p(E_{Fn(Fp)}) \times E_{Fn(Fp)}^p \equiv \int_{-\infty}^{\infty} E^p \times \left(-\frac{\partial f}{\partial E} \right) dE, \quad -\frac{\partial f}{\partial E} = \frac{1}{k_B T} \times \frac{e^\gamma}{(1+e^\gamma)^2}.$$

Further, one notes that, at 0 K, $-\frac{\partial f}{\partial E} = \delta(E - E_{Fno(Fpo)})$, $\delta(E - E_{Fno(Fpo)})$ being the Dirac delta (δ)-function. Therefore, $G_p(E_{Fno(Fpo)}) = 1$.

Then, at low T, by a variable change $\gamma \equiv (E - E_{Fn(Fp)})/(k_B T)$, one has:

$$G_p(E_{Fn(Fp)}) \equiv 1 + E_{Fn(Fp)}^{-p} \times \int_{-\infty}^{\infty} \frac{e^y}{(1+e^y)^2} \times (k_B T y + E_{Fn(Fp)})^p dy = 1 + \sum_{\mu=1,2,\dots}^p C_p^\beta \times (k_B T)^\beta \times E_{Fn(Fp)}^{-\beta} \times I_\beta$$

where $C_p^\beta \equiv p(p-1) \dots (p-\beta+1)/\beta!$ and the integral I_β is given by:

$I_\beta = \int_{-\infty}^{\infty} \frac{y^\beta \times e^y}{(1+e^y)^2} dy = \int_{-\infty}^{\infty} \frac{y^\beta}{(e^{y/2} + e^{-y/2})^2} dy$, vanishing for odd values of β . Then, for even values of $\beta = 2n$, with $n=1, 2, \dots$, one obtains:

$$I_{2n} = 2 \int_0^{\infty} \frac{y^{2n} \times e^y}{(1+e^y)^2} dy.$$

Now, using an identity $(1+e^y)^{-2} \equiv \sum_{s=1}^{\infty} (-1)^{s+1} s \times e^{y(s-1)}$, a variable change: $sy = -t$, the Gamma function: $\int_0^{\infty} t^{2n} e^{-t} dt \equiv \Gamma(2n+1) = (2n)!$, and also the definition of the Riemann's zeta function: $\zeta(2n) \equiv 2^{2n-1} \pi^{2n} |B_{2n}| / (2n)!$, B_{2n} being the Bernoulli numbers, one finally gets: $I_{2n} = (2^{2n} - 2) \times \pi^{2n} \times |B_{2n}|$. So, from above Eq. of $\langle E^p \rangle_{FDDF}$, we get in the degenerate case the following ratio:

$$G_p(E_{Fn(Fp)}) \equiv \frac{\langle E^p \rangle_{FDDF}}{E_{Fn(Fp)}^p} = 1 + \sum_{n=1}^p \frac{p(p-1) \dots (p-2n+1)}{(2n)!} \times (2^{2n} - 2) \times |B_{2n}| \times y^{2n} \equiv G_{p \geq 1}(y), \quad (12)$$

$$\text{Where } y \equiv \frac{\pi}{\xi_{n(p)}(N^*, T)} = \frac{\pi k_B T}{E_{Fn(Fp)}(N^*, T)}.$$

Then, some usual results of $G_{p \geq 1}(y)$ are given in Table 2 in Appendix 1, being needed to determine all the following electrical-and-thermoelectric properties.

ELECTRICAL-AND-THERMOELECTRIC PROPERTIES

Here, if denoting, for majority electrons (holes), the electrical conductivity by $\sigma(N, r_{d(a)}, x, T)$ expressed in $\text{ohm}^{-1} \times \text{cm}^{-1}$, the thermal conductivity by $\kappa(N, r_{d(a)}, x, T)$ in $\frac{W}{\text{cm} \times K}$, and the

Lorenz number L defined by:

$$L = \frac{\pi^2}{3} \times \left(\frac{k_B}{q} \right)^2 = 2.4429637 \left(\frac{W \times \text{ohm}}{K^2} \right) = 2.4429637 \times 10^{-8} (V^2 \times K^{-2}), \text{ then the well-}$$

known Wiedemann-Frank law states that the ratio, $\frac{\kappa}{\sigma}$, is proportional to the temperature $T(K)$,

as:

$$\frac{\kappa(N, r_{d(a)}, x, T)}{\sigma(N, r_{d(a)}, x, T)} = L \times T. \quad (13)$$

We now determine the general form of σ in the following.

First of all, it is expressed in terms of the kinetic energy of the electron (hole),

$$E_k \equiv \frac{\hbar^2 \times k^2}{2 \times m_{c(v)}(x) \times m_0}, \text{ or the wave number } k, \text{ as:}$$

$$\sigma(k) \equiv \frac{q^2 \times k}{\pi \times \hbar} \times \frac{k}{k_{sn(sp)}} \times [k \times a_{Bn(Bp)}] \times \left(\frac{E_k}{\eta_{n(p)}} \right)^{1/2},$$

Which is thus proportional to E_k^2 .

Then, for $E \geq 0$, we obtain: $\langle E^2 \rangle_{FDDF} \equiv G_2(y = \frac{\pi k_B T}{E_{Fn(Fp)}}) \times E_{Fn(Fp)}^2$, and

$G_2(y) = \left(1 + \frac{y^2}{3}\right) \equiv G_2(N, r_{d(a)}, x, T)$, with $y \equiv \frac{\pi}{\xi_{n(p)}}$, $\xi_{n(p)} = \xi_{n(p)}(N, r_{d(a)}, x, T)$ for a presentation simplicity. Therefore, one obtains^[1]:

$$\sigma(N, r_{d(a)}, x, T) \equiv \left[\frac{q^2}{\pi \times \hbar} \times \frac{k_{Fn(Fp)}(N^*)}{R_{sn(sp)}(N^*)} \times [k_{Fn(Fp)}(N^*) \times a_{Bn(Bp)}(r_{d(a)})] \times \sqrt{A_{n(p)}(N^*)} \right] \times \left[G_2(N, r_{d(a)}, x, T) \times \left(\frac{E_{Fn(Fp)}(N, r_{d(a)}, x, T)}{E_{Fno(Fpo)}(N^*)} \right)^2 \right] \left(\frac{1}{ohm \times cm} \right),$$

$$\frac{q^2}{\pi \times \hbar} = 7.7480735 \times 10^{-5} \text{ ohm}^{-1}, A_{n(p)}(N^*) = \frac{E_{Fno(Fpo)}(N^*)}{\eta_{n(p)}(N^*)}, R_{sn(sp)}(N^*) \equiv \frac{k_{sn(sp)}}{k_{Fn(Fp)}}, (14)$$

Which can be used to define the resistivity as: $\rho(N, r_{d(a)}, x, T) \equiv 1/\sigma(N, r_{d(a)}, x, T)$, noting again that $N^* \equiv N - N_{CDn(NDp)}(r_{d(a)}, x)$. This $\sigma(N, r_{d(a)}, x, T)$ -result is an essential one in this paper, being used to determine other electrical-and-thermoelectric properties.

In Eq. (14), one notes that at $T = 0 \text{ K}$, $\sigma(N, r_{d(a)}, x, T = 0 \text{ K})$ is proportional to $E_{Fno(Fpo)}^2$, or to $(N^*)^{\frac{4}{3}}$. Thus, $\sigma(N = N_{CDn(NDp)}, r_{d(a)}, x, T = 0 \text{ K}) = 0$ at $N^* = 0$, at which the metal-insulator transition (MIT) occurs.

Electrical Coefficients

The relaxation time τ is related to σ by^[1]:

$\tau(N, r_{d(a)}, x, T) \equiv \sigma(N, r_{d(a)}, x, T) \times \frac{m_{c(v)}(x) \times m_0}{q^2 \times (N^* / \xi_{c(v)})}$. Therefore, the mobility μ is given by:

$$\mu(N, r_{d(a)}, x, T) \equiv \mu(N^*, r_{d(a)}, T) = \frac{q \times \tau(N, r_{d(a)}, x, T)}{m_{c(v)}(x) \times m_0} = \frac{\sigma(N, r_{d(a)}, x, T)}{q \times (N^* / \xi_{c(v)})} \left(\frac{cm^2}{V \times s} \right). \quad (15)$$

Here, at $T = 0 \text{ K}$, $\mu(N^*, r_{d(a)}, T)$ is thus proportional to $(N^*)^{1/3}$, since $\sigma(N^*, r_{d(a)}, T = 0 \text{ K})$ is proportional to $(N^*)^{4/3}$. Thus, $\mu(N^* = 0, r_{d(a)}, T = 0 \text{ K}) = 0$ at $N^* = 0$, at which the metal-insulator transition (MIT) occurs.

Then, since τ and σ are both proportional to $E_{Fn(Fp)}(N^*, T)^2$, as given above, the Hall factor is defined by:

$r_H(N, r_{d(a)}, x, T) \equiv \frac{(\tau^2)_{FDDF}}{[(\tau)_{FDDF}]^2} = \frac{G_4(y)}{[G_2(y)]^2}$, $y \equiv \frac{\pi}{\xi_{n(p)}(N, r_{d(a)}, x, T)} = \frac{\pi k_B T}{E_{Fn(Fp)}(N, r_{d(a)}, x, T)}$, and therefore, the Hall mobility yields:

$$\mu_H(N, r_{d(a)}, x, T) \equiv \mu(N, r_{d(a)}, x, T) \times r_H(N^*, T) \left(\frac{cm^2}{V \times s} \right), \quad (16)$$

Noting that, at $T=0K$, since $r_H(N, r_{d(a)}, x, T) = 1$, one then gets:
 $\mu_H(N, r_{d(a)}, x, T) \equiv \mu(N, r_{d(a)}, x, T)$.

Our generalized Einstein relation

Our generalized Einstein relation is found to be defined as ^[1]:

$$\frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} \equiv \frac{N^*}{q} \times \frac{dE_{Fn(Fp)}}{dN^*} \equiv \frac{k_B \times T}{q} \times \left(u \frac{d\xi_{n(p)}(u)}{du} \right) = \sqrt{\frac{3 \times L}{\pi^2}} \times T \times \left(u \frac{d\xi_{n(p)}(u)}{du} \right), \quad \frac{k_B}{q} = \sqrt{\frac{3 \times L}{\pi^2}} \quad (17)$$

Where $D(N, r_{d(a)}, x, T)$ is the diffusion coefficient, $\xi_{n(p)}(u)$ is defined in Eq. (11), and the mobility $\mu(N, r_{d(a)}, x, T)$ is determined in Eq. (15). Then, by differentiating this function $\xi_{n(p)}(u)$ with respect to u , one thus obtains $\frac{d\xi_{n(p)}(u)}{du}$. Therefore, Eq. (17) can also be rewritten as:

$$\frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} = \frac{k_B \times T}{q} \times u \frac{V'(u) \times W(u) - V(u) \times W'(u)}{W^2(u)},$$

Where $W'(u) = ABu^{B-1}$ and $V'(u) = u^{-1} + 2^{-\frac{s}{2}} e^{-du}(1 - du) + \frac{2}{s} Au^{B-1} F(u) \left[\left(1 + \frac{sB}{2}\right) + \frac{4}{s} \times \frac{bu^{-\frac{4}{s}} + 2cu^{-\frac{s}{s}}}{1 + bu^{-\frac{4}{s}} + cu^{-\frac{s}{s}}} \right]$.

One remarks that: (i) as $u \rightarrow 0$, one has: $W^2 \simeq 1$ and $u[V' \times W - V \times W'] \simeq 1$, and therefore: $\frac{D_{n(p)}(u)}{\mu} \simeq \frac{k_B \times T}{q}$, and (ii) as $u \rightarrow \infty$, one has: $W^2 \approx A^2 u^{2B}$ and $u[V' \times W - V \times W'] \approx \frac{2}{s} au^{2/3} A^2 u^{2B}$, and therefore, in this **highly degenerate case** and at $T=0K$, the **above generalized Einstein relation** is reduced to the **usual Einstein one**:

$\frac{D(N, r_{d(a)}, x, T=0 K)}{\mu(N, r_{d(a)}, x, T=0 K)} \approx \frac{2}{3} E_{Fno(Fpo)}(N^*)/q$. In other words, **Eq. (17) verifies the correct limiting conditions**.

Furthermore, in the present degenerate case ($u \gg 1$), Eq. (17) gives:

$$\frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} \simeq \frac{2}{3} \times \frac{E_{Fno}(F_{po})(u)}{q} \times \left[1 + \frac{4}{3} \times \frac{\left(bu^{-\frac{4}{3}} + 2cu^{-\frac{8}{3}} \right)}{\left(1 + bu^{-\frac{4}{3}} + cu^{-\frac{8}{3}} \right)} \right], \quad (18)$$

Where $a = [3\sqrt{\pi}/4]^{2/3}$, $b = \frac{1}{8} \left(\frac{\pi}{a} \right)^2$ and $c = \frac{62.3739855}{1920} \left(\frac{\pi}{a} \right)^4$.

In Tables 3n(3p) given in Appendix 1, for given x , $N > N_{CDn(CDp)}$ and $T(=4.5 \text{ K and } 77 \text{ K})$, and from Equations (14, 15, 16, 17), the numerical results of the coefficients: σ , μ , μ_H and D are found to be decreased with increasing $r_{d(a)}$, respectively.

Thermoelectric Coefficients

First of all, from Eq. (14), obtained for $\sigma(N, r_{d(a)}, x, T)$, the well-known Mott definition for the thermoelectric power or for the Seebeck coefficient, S , is found to be given by:

$$S(N, r_{d(a)}, x, T) \equiv \frac{-\pi^2}{3} \times \frac{k_B}{q} \times k_B T \times \left. \frac{\partial \ln \sigma(E)}{\partial E} \right|_{E=E_{Fn}(F_p)} = \frac{-\pi^2}{3} \times \frac{k_B}{q} \times \frac{\partial \ln \sigma(\xi_{n(p)})}{\partial \xi_{n(p)}}.$$

Then, using Eq. (11), for the degenerate case, $\xi_{n(p)} \geq 0$, one gets, by putting

$$F_S(N, r_{d(a)}, x, T) \equiv \left[1 - \frac{y^2}{3 \times G_2 \left(y = \frac{\pi}{\xi_{n(p)}} \right)} \right],$$

$$S(N, r_{d(a)}, x, T) \equiv \frac{-\pi^2}{3} \times \frac{k_B}{q} \times \frac{2F_{Sb}(N^*, T)}{\xi_{n(p)}} = -\sqrt{\frac{3 \times L}{\pi^2}} \times \frac{2 \times \xi_{n(p)}}{\left(1 + \frac{3 \times \xi_{n(p)}^2}{\pi^2} \right)} =$$

$$-2\sqrt{L} \times \frac{\sqrt{(ZT)_{Mott}}}{1 + (ZT)_{Mott}} \left(\frac{V}{K} \right) < 0, \quad (ZT)_{Mott} = \frac{\pi^2}{3 \times \xi_{n(p)}^2}, \quad (19)$$

according to:

$$\frac{\partial S}{\partial \xi_{n(p)}} = \sqrt{\frac{3 \times L}{\pi^2}} \times 2 \times \frac{\frac{3 \times \xi_{n(p)}^2}{\pi^2} - 1}{\left(1 + \frac{3 \times \xi_{n(p)}^2}{\pi^2} \right)^2} = \sqrt{\frac{3 \times L}{\pi^2}} \times 2 \times \frac{(ZT)_{Mott} \times [1 - (ZT)_{Mott}]}{[1 + (ZT)_{Mott}]^2}.$$

Here, one notes that: (i) as $\xi_{n(p)} \rightarrow +\infty$ or $\xi_{n(p)} \rightarrow +0$, one has a same limiting value of S :

$S \rightarrow -0$, (ii) at $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, since $\frac{\partial S}{\partial \xi_{n(p)}} = 0$, one therefore gets: a minimum

$(S)_{min.} = -\sqrt{L} \simeq -1.563 \times 10^{-4} \left(\frac{V}{K} \right)$, and (iii) at $\xi_{n(p)} = 1$ one obtains:
 $S \simeq -1.322 \times 10^{-4} \left(\frac{V}{K} \right).$

Further, the figure of merit, ZT, is found to be defined by:

$$ZT(N, r_{d(a)}, x, T) \equiv \frac{S^2 \times \sigma \times T}{\kappa} = \frac{S^2}{L} = \frac{4 \times (ZT)_{Mott}}{[1 + (ZT)_{Mott}]^2}. \quad (20)$$

Here, one notes that: (i) $\frac{\partial(ZT)}{\partial \xi_{n(p)}} = 2 \times \frac{S}{L} \times \frac{\partial S}{\partial \xi_{n(p)}}$, $S < 0$, (ii) at $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, since $\frac{\partial(ZT)}{\partial \xi_{n(p)}} = 0$, one gets: a maximum $(ZT)_{max} = 1$, and $(ZT)_{Mott} = 1$, and (iii) at $\xi_{n(p)} = 1$, one obtains: $ZT \simeq 0.715$ and $(ZT)_{Mott} = \frac{\pi^2}{3} \simeq 3.290$.

Finally, the first Van-Cong coefficient, VC1, can be defined by:

$$VC1(N, r_{d(a)}, x, T) \equiv -N^* \times \frac{dS}{dN^*} \left(\frac{V}{K} \right) = N^* \times \frac{\partial S}{\partial \xi_{n(p)}} \times -\frac{\partial \xi_{n(p)}}{\partial N^*}, \text{ being equal to } 0 \text{ for } \xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}, \quad (21)$$

and the second Van-Cong coefficient, VC2, as:

$$VC2(N, r_{d(a)}, x, T) \equiv T \times VC1(V), \quad (22)$$

the Thomson coefficient, Ts, by:

$$Ts(N, r_{d(a)}, x, T) \equiv T \times \frac{dS}{dT} \left(\frac{V}{K} \right) = T \times \frac{\partial S}{\partial \xi_{n(p)}} \times \frac{\partial \xi_{n(p)}}{\partial T}, \text{ being equal to } 0 \text{ for } \xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}, \quad (23)$$

and the Peltier coefficient, Pt, as:

$$Pt(N, r_{d(a)}, x, T) \equiv T \times S(V). \quad (24)$$

One notes here that in next Tables 5n(p) and 6n(p) given in Appendix 1, obtained with such given physical conditions N (or T) for the decreasing $\xi_{n(p)}$, since $VC1(N, r_{d(a)}, x, T)$ and

$Ts(N, r_{d(a)}, x, T)$ are expressed in terms of $\frac{-dS}{dN^*}$ and $\frac{dS}{dT}$, one has: $[VC1, Ts] < 0$ for $\xi_{n(p)} > \sqrt{\frac{\pi^2}{3}}$, $[VC1, Ts] = 0$ for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}$, and $[VC1, Ts] > 0$ for $\xi_{n(p)} < \sqrt{\frac{\pi^2}{3}}$, stating also that for

$$\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}:$$

(i) S, determined in Eq. (19), thus presents a same minimum $(S)_{min.} = -\sqrt{L} \simeq -1.563 \times 10^{-4} \left(\frac{V}{K} \right)$,

(ii) ZT, determined in Eq. (20), therefore presents a **same maximum**: $(ZT)_{\max} = 1$, since the variations of ZT are expressed in terms of $[VC1, Ts] \times S$, $S < 0$.

Furthermore, it is interesting to remark that the (VC2)-coefficient is related to our generalized Einstein relation (17) by:

$$\frac{k_B}{q} \times VC2(N, r_{d(a)}, x, T) \equiv -\frac{\partial S}{\partial \xi_{n(p)}} \times \frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} \left(\frac{V^2}{K} \right), \quad \frac{k_B}{q} = \sqrt{\frac{3 \times L}{\pi^2}}, \quad (25)$$

according, in this work, with the use of our Eq. (21), to:

$$VC2(N, r_{d(a)}, x, T) \equiv -\frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} \times 2 \times \frac{(ZT)_{\text{Mott}} \times [1 - (ZT)_{\text{Mott}}]}{[1 + (ZT)_{\text{Mott}}]^2} \quad (V).$$

Of course, our relation (25) is reduced to: $\frac{D}{\mu}$, VC1 and VC2, being determined respectively by Equations (17, 21, 22).

Now, in the degenerate n(p)-type $X(x)$ – alloy, and for $N > N_{CDn(CDp)}$, and for $T=3K$ (80K), the numerical results of various thermoelectric coefficients are reported in Tables 4n(4p) in Appendix 1, noting that their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease), respectively.

Then, in Tables 5n(5p) given Appendix 1 for a given N and with increasing T , and in Tables 6n(6p) given Appendix 1 for a given T and with decreasing N , the reduced Fermi-energy $\xi_{n(p)}$ decreases, and various thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘).

CONCLUDING REMARKS

Here, some concluding remarks are given as follows.

(1) In $n^+(p^+) - p(n) X(x)[Y(x)]$ - crystalline alloys, $0 \leq x \leq 1$, the electrical-and-thermoelectric laws, relations, and various coefficients are found to be enhanced by our static dielectric constant law, $\epsilon(r_{d(a)}, x)$, being, for a given x , decreased with increasing $r_{d(a)}$, as that given in Tables 7 and 8 of our recent work [3], by our accurate Fermi energy, $E_{Fn(Fp)}$, being given in Eq. (11), and in particular by our electrical conductivity model, being given in Eq. (14).

(2) The generalized Mott criterium in the MIT is expressed in Equations (3, 5, 6), stating that the critical impurity density $N_{CDn(CDp)}$ is just the density of electrons (holes), localized in the

exponential conduction (valence)-band tail, $N_{CDn(CDp)}^{EBT}$, obtained with a precision of the order of $2.82 (2.88) \times 10^{-7}$, respectively, as those given in Tables 7 and 8 of our previous work^[3], and the effective electron (hole)-density can be defined by: $N^* \equiv N - N_{CDn(CDp)} \simeq N - N_{CDn(CDp)}^{EBT}$, as that observed in the compensated crystals. This should be a **new result**.

(3) The ratio of the inverse effective screening length $k_{sn(sp)}$ to Fermi wave number $k_{Fn(kp)}$ at 0 K, $R_{sn(sp)}(N^*)$, defined in Eq. (7), is valid for any density N^* . This should be a **new result**.

(4) In Tables 5n(5p) given Appendix 1, for a given impurity density N and with increasing temperature T , and then in Tables 6n(6p) given Appendix 1, for a given T and with decreasing N , the reduced Fermi-energy $\xi_{n(p)}$ decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows by: (increase: $\nearrow$, decrease: $\searrow$). One remarks in these Tables that, for any given x , $r_{d(a)}$ and N (or T), with increasing T (or decreasing N), one obtains: (i) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, while the numerical results of the Seebeck coefficient S present a **same minimum** $(S)_{min.} = -\sqrt{L} \simeq -1.563 \times 10^{-4} \left(\frac{V}{K}\right)$, those of the figure of merit ZT show a **same maximum** $(ZT)_{max.} = 1$, (ii) for $\xi_{n(p)} = 1$, the numerical results of S , ZT , the Mott figure of merit $(ZT)_{Mott}$, the Van-Cong coefficient $VC1$, and the Thomson coefficient Ts , present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715 , 3.290 , $1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$, respectively, and finally (iii) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, $(ZT)_{Mott} = 1$. It seems that these same results could represent a **new law in the thermoelectric properties, obtained in the degenerate case**.

(5) Finally, our electrical-and-thermoelectric relation is given in Eq. (25) by:

$\frac{k_B}{q} \times VC2(N, r_{d(a)}, x, T) \equiv -\frac{\partial S}{\partial \xi_{n(p)}} \times \frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} \left(\frac{V^2}{K}\right)$, $\frac{k_B}{q} = \sqrt{\frac{3 \times L}{\pi^2}}$, according, in this work, to:

$VC2(N, r_{d(a)}, x, T) \equiv -\frac{D(N, r_{d(a)}, x, T)}{\mu(N, r_{d(a)}, x, T)} \times 2 \times \frac{(ZT)_{Mott} \times [1 - (ZT)_{Mott}]}{[1 + (ZT)_{Mott}]^2} (V)$, being reduced to: $\frac{D}{\mu}$, $VC1$ and $VC2$, determined respectively in Equations (17, 21, 22). This should be a **new result**.

REFERENCES

1. Van Cong H. Various Electrical-and-Thermoelectric Laws, Relations, and Coefficients in New n(p)-type Degenerate “Compensated” GaAs(1-x)P(x)-Crystalline Alloy, Enhanced by Our Static Dielectric Constant Law and Electrical Conductivity Model (XI). WJERT, 2025; 11(4): 207-238.
2. Van Cong H. 27.62 % (26.99 %)-Highest Efficiencies in CdTe(1-x)TSe(x) Crystalline Alloy Junction Solar Cells at 300 K, According to Highest Hot Reservoir Temperatures, 455.8 K (410.9 K), obtained from Carnot-Efficiency Theorem (XV). WJERT, 2024; 10(6): 253-271.
3. Van Cong, H. New Critical Impurity Density in Metal-Insulator Transition, obtained in Various n(p)-Type Degenerate Crystalline Alloys, being Just That of Carriers Localized in Exponential Band Tails (II). WJERT, 2024; 10(4): 65-96.
4. Van Cong H. Same maximum figure of merit $ZT(=1)$, due to the effect of impurity size, obtained in the n(p)-type
5. Degenerate Ge-crystal ($\xi_{n(p)} \geq 1$), at same reduced Fermi Energy $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, same minimum Seebeck coefficient $(S)_{\min.} \left(\simeq -1.563 \times 10^{-4} \frac{V}{K} \right)$, same maximum $(ZT)_{\max.} = 1$, and same $(ZT)_{\text{Mott}} \left(= \frac{\pi^2}{3\xi_{n(p)}^2} = 1 \right)$, SCIREA Journal of Physics, 2023; 8(4): 407-430.
6. Van Cong, H. Same Maximal Figure of Merit $ZT(=1)$, Due to the Effect of Impurity Size, Obtained in the n(p)-Type Degenerate Si-Crystal ($\xi_{n(p)} \geq 1$), at Same Reduced Fermi Energy $\xi_{n(p)} (= 1.8138)$ and Same Minimum Seebeck Coefficient $s \left(= -1.563 \times 10^{-4} \frac{V}{K} \right)$, at which Same $(ZT)_{\text{Mott}} \left(= \frac{\pi^2}{3\xi_{n(p)}^2} = 1 \right)$. SCIREA Journal of Physics, 2023; 8(2): 66-90.
7. Van Cong, H. Effects of donor size and heavy doping on optical, electrical and thermoelectric properties of various degenerate donor-silicon systems at low temperatures. American Journal of Modern Physics, 2018; 7(4): 136-165.
8. Kim, H. S. et al. Characterization of Lorenz number with Seebeck coefficient measurement. APL Materials, 2015; 3(4): 041506.

9. Hyun, B. D. et al. Electrical-and-Thermoelectric Properties of $90\%Bi_2Te_3 - 5\%Sb_2Te_3 - 5\%Sb_2Se_3$ Single Crystals Doped with SbI_3 . Scripta Materialia, 1998; 40(1): 49-56.
10. Van Cong, H. and Debiais, G. A simple accurate expression of the reduced Fermi energy for any reduced carrier density. J. Appl. Phys., 1993; 73: 1545-1546.
11. Van Cong, H. et al. Size effect on different impurity levels in semiconductors. Solid State Communications, 1984; 49: 697-699.
12. Van Cong, H. Diffusion coefficient in degenerate semiconductors. Phys. Stat. Sol. (b), 1984; 101: K27.
13. Van Cong, H. and Doan Khanh, B. Simple accurate general expression of the Fermi-Dirac integral $F_j(a)$ and for $j > -1$. Solid-State Electron., 1992; 35(7): 949-951.
14. Van Cong, H. New series representation of Fermi-Dirac integral $F_j(-\infty < a < \infty)$ for arbitrary $j > -1$, and its effect on $F_j(a \geq 0_+)$ for integer $j \geq 0$. Solid-State Electron., 1991; 34(5): 489-492.

APPENDIX 1

Table 1: In these X(x)-and-Y(x) crystalline alloys, their different values of energy-band-structure parameters, for a given x, are given in the following.

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy, in which $r_{\text{do(ao)}} = r_{\text{Te(Cd)}} = 0.132 \text{ nm}$ (**0.148 nm**), we have [3]:

$$g_{\text{c(v)}}(x) = 1(1) \times x + 1(1) \times (1-x) = 1$$
 , $m_{\text{c(v)}}(x)/m_0 = 0.197 (0.801) \times x + 0.095 (0.82) \times (1-x)$,
 $\varepsilon_0(x) = 9 \times x + 10.31 \times (1-x)$, $E_{\text{go}}(x) = 2.58 \times x + 1.62 \times (1-x)$.

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x$ -crystalline alloy, in which $r_{\text{do(ao)}} = r_{\text{Te(Cd)}} = 0.132 \text{ nm}$ (**0.148 nm**), we have [3]:

$$g_{\text{c(v)}}(x) = 1(1) \times x + 1(1) \times (1-x) = 1$$
 , $m_{\text{c(v)}}(x)/m_0 = 0.11 (0.45) \times x + 0.095 (0.82) \times (1-x)$,
 $\varepsilon_0(x) = 10.2 \times x + 10.31 \times (1-x)$, $E_{\text{go}}(x) = 1.84 \times x + 1.62 \times (1-x)$.

Table 2: Expressions for $G_{p \geq 1}(y \equiv \frac{\pi}{\xi_{\text{n(p)}}})$, due to the Fermi-Dirac distribution function, noting that $G_{p=1}(y \equiv \frac{\pi k_B T}{E_{\text{Fn(Fp)}}} = \frac{\pi}{\xi_{\text{n(p)}}}) = 1$, used to determine the electrical-and-thermoelectric coefficients.

$G_{3/2}(y)$	$G_2(y)$	$G_{5/2}(y)$	$G_3(y)$	$G_{7/2}(y)$	$G_4(y)$	$G_{9/2}(y)$
$(1 + \frac{y^2}{8} + \frac{7y^4}{640})$	$(1 + \frac{y^2}{3})$	$(1 + \frac{5y^2}{8} - \frac{7y^4}{384})$	$(1 + y^2)$	$(1 + \frac{35y^2}{24} + \frac{49y^4}{384})$	$(1 + 2y^2 + \frac{7y^4}{15})$	$(1 + \frac{21y^2}{8} + \frac{147y^4}{128})$

Table 3n

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy, one notes that, for given x, $N > 2N_{\text{CDn}}$ and T(=4.5 K and 77 K), the functions: σ, μ, μ_H, D , expressed respectively in $(\frac{10^5}{\text{ohm} \times \text{cm}}, \frac{10^5 \times \text{cm}^2}{\text{V} \times \text{s}}, \frac{10^5 \times \text{cm}^2}{\text{V} \times \text{s}}, \frac{10^2 \times \text{cm}^2}{\text{s}})$, decrease with increasing r_d .

Donor	P	As	Sb	Sn
r_d (nm)	0.110	0.118	0.136	0.140

For x=0, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
4	3.16, 4.943, 4.943, 1.48	2.75, 4.294, 4.294, 1.28	2.50, 3.905, 3.905, 1.17	2.44, 3.821, 3.821, 1.14
6	4.60, 4.786, 4.786, 1.87	3.99, 4.152, 4.152, 1.63	3.62, 3.772, 3.772, 1.48	3.54, 3.690, 3.690, 1.44
10	7.38, 4.610, 4.610, 2.54	6.39, 3.993, 3.993, 2.20	5.80, 3.623, 3.623, 1.99	5.67, 3.543, 3.543, 1.95

For x=0.5, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
4	1.35, 2.115, 2.115, 0.41	1.18, 1.851, 1.851, 0.36	1.07, 1.692, 1.692, 0.33	1.05, 1.658, 1.658, 0.32
6	1.94, 2.026, 2.026, 0.51	1.69, 1.769, 1.769, 0.45	1.54, 1.614, 1.614, 0.41	1.51, 1.581, 1.581, 0.40
10	3.08, 1.928, 1.928, 0.69	2.68, 1.679, 1.679, 0.60	2.44, 1.530, 1.530, 0.55	2.39, 1.498, 1.498, 0.53

For x=1, the values of (σ, μ, μ_H, D) at **4.5 K**

4	0.73, 1.161, 1.161, 0.16	0.64, 1.024, 1.024, 0.14	0.59, 0.941, 0.941, 0.13	0.57, 0.923, 0.923, 0.13
6	1.04, 1.099, 1.099, 0.21	0.91, 0.966, 0.966, 0.18	0.83, 0.886, 0.886, 0.16	0.82, 0.869, 0.869, 0.16
10	1.64, 1.032, 1.032, 0.27	1.43, 0.904, 0.904, 0.23	1.31, 0.827, 0.827, 0.22	1.28, 0.810, 0.810, 0.21

For x=0, the values of (σ, μ, μ_H, D) at **77 K**

N (10^{19} cm^{-3})				
4	3.17, 4.949, 4.963, 1.48	2.75, 4.300, 4.312, 1.28	2.50, 3.910, 3.921, 1.17	2.45, 3.826, 3.837, 1.14
6	4.60, 4.789, 4.797, 1.88	3.99, 4.155, 4.162, 1.63	3.62, 3.775, 3.781, 1.48	3.54, 3.692, 3.699, 1.45
10	7.38, 4.611, 4.615, 2.54	6.39, 3.994, 3.998, 2.20	5.80, 3.624, 3.628, 2.00	5.67, 3.545, 3.548, 1.95

For $x=0.5$, the values of (σ, μ, μ_H, D) at 77 K

N (10^{19} cm^{-3})				
4	1.35, 2.122, 2.136, 0.41	1.18, 1.857, 1.869, 0.36	1.08, 1.697, 1.709, 0.33	1.05, 1.663, 1.674, 0.32
6	1.94, 2.030, 2.038, 0.52	1.69, 1.772, 1.779, 0.45	1.54, 1.617, 1.624, 0.41	1.51, 1.584, 1.590, 0.40
10	3.08, 1.930, 1.934, 0.69	2.68, 1.681, 1.684, 0.60	2.44, 1.531, 1.534, 0.55	2.39, 1.499, 1.502, 0.54

For $x=1$, the values of (σ, μ, μ_H, D) at 77 K

N (10^{19} cm^{-3})				
4	0.73, 1.167, 1.182, 0.17	0.64, 1.030, 1.043, 0.15	0.59, 0.946, 0.959, 0.13	0.58, 0.928, 0.940, 0.13
6	1.05, 1.102, 1.110, 0.21	0.92, 0.969, 0.976, 0.18	0.84, 0.889, 0.895, 0.16	0.82, 0.871, 0.878, 0.16
10	1.64, 1.034, 1.037, 0.27	1.44, 0.906, 0.909, 0.24	1.31, 0.828, 0.832, 0.22	1.28, 0.812, 0.815, 0.21

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x$ - alloy, one notes that, for given x , $N > N_{CDn}$ and $T(=4.5 \text{ K and } 77 \text{ K})$, the functions: σ, μ, μ_H, D , expressed respectively in $\left(\frac{10^4}{\text{ohm}\times\text{cm}}, \frac{10^3 \times \text{cm}^2}{\text{V}\times\text{s}}, \frac{10^3 \times \text{cm}^2}{\text{V}\times\text{s}}, \frac{10^3 \times \text{cm}^2}{\text{s}}\right)$, decrease with increasing r_d .

Donor r_d (nm)	P 0.110	As 0.118	Sb 0.136	Sn 0.140
---------------------	------------	-------------	-------------	-------------

For $x=0$, the values of (σ, μ, μ_H, D) at 4.5 K

N (10^{19} cm^{-3})				
4	3.16, 4.943, 4.943, 1.48	2.75, 4.294, 4.294, 1.28	2.50, 3.905, 3.905, 1.17	2.44, 3.821, 3.821, 1.14
6	4.60, 4.786, 4.786, 1.87	3.99, 4.152, 4.152, 1.63	3.62, 3.772, 3.772, 1.48	3.54, 3.690, 3.690, 1.44
10	7.38, 4.610, 4.610, 2.54	6.39, 3.993, 3.993, 2.20	5.80, 3.623, 3.623, 1.99	5.67, 3.543, 3.543, 1.95

For $x=0.5$, the values of (σ, μ, μ_H, D) at 4.5 K

N (10^{19} cm^{-3})				
4	2.74, 4.288, 4.288, 1.19	2.38, 3.729, 3.729, 1.03	2.17, 3.394, 3.394, 0.94	2.12, 3.321, 3.321, 0.92
6	3.98, 4.146, 4.146, 1.50	3.45, 3.600, 3.600, 1.31	3.14, 3.272, 3.272, 1.19	3.07, 3.201, 3.201, 1.16
10	6.38, 3.987, 3.987, 2.03	5.53, 3.456, 3.456, 1.76	5.02, 3.138, 3.138, 1.60	4.91, 3.069, 3.069, 1.57

For $x=1$, the values of (σ, μ, μ_H, D) at 4.5 K

N (10^{19} cm^{-3})				
4	2.40, 3.758, 3.758, 0.97	2.09, 3.271, 3.271, 0.84	1.90, 2.979, 2.979, 0.77	1.86, 2.916, 2.916, 0.75
6	3.48, 3.628, 3.628, 1.23	3.02, 3.153, 3.153, 1.07	2.75, 2.868, 2.868, 0.97	2.69, 2.806, 2.806, 0.95
10	5.58, 3.483, 3.483, 1.66	4.84, 3.022, 3.022, 1.44	4.39, 2.745, 2.745, 1.30	4.29, 2.685, 2.685, 1.28

For $x=0$, the values of (σ, μ, μ_H, D) at 77 K

N (10^{19} cm^{-3})				
4	3.17, 4.949, 4.963, 1.48	2.75, 4.300, 4.312, 1.28	2.50, 3.910, 3.921, 1.17	2.45, 3.826, 3.837, 1.14
6	4.60, 4.789, 4.797, 1.88	3.99, 4.155, 4.162, 1.63	3.62, 3.775, 3.781, 1.48	3.54, 3.692, 3.699, 1.45
10	7.38, 4.611, 4.615, 2.54	6.39, 3.994, 3.998, 2.20	5.80, 3.624, 3.628, 2.00	5.67, 3.545, 3.548, 1.95

For $x=0.5$, the values of (σ, μ, μ_H, D) at 77 K

$N (10^{19} \text{ cm}^{-3})$				
4	2.75, 4.294, 4.308, 1.19	2.39, 3.735, 3.747, 1.03	2.17, 3.398, 3.410, 0.94	2.12, 3.326, 3.337, 0.92
6	3.98, 4.149, 4.157, 1.51	3.46, 3.603, 3.610, 1.31	3.14, 3.275, 3.281, 1.19	3.07, 3.204, 3.210, 1.16
10	6.38, 3.988, 3.992, 2.04	5.53, 3.457, 3.461, 1.76	5.02, 3.139, 3.142, 1.60	4.91, 3.070, 3.073, 1.57

For $x=1$, the values of (σ, μ, μ_H, D) at 77 K

$N (10^{19} \text{ cm}^{-3})$				
4	2.41, 3.764, 3.779, 0.97	2.09, 3.277, 3.290, 0.84	1.91, 2.984, 2.996, 0.77	1.86, 2.921, 2.932, 0.75
6	3.49, 3.632, 3.640, 1.23	3.03, 3.156, 3.163, 1.07	2.75, 2.871, 2.877, 0.97	2.69, 2.809, 2.815, 0.95
10	5.58, 3.485, 3.489, 1.66	4.84, 3.023, 3.027, 1.44	4.39, 2.746, 2.749, 1.30	4.30, 2.686, 2.689, 1.28

Table 3p:

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy, one notes that, for given x , $N > 2N_{CDP}$ and $T(=4.5 \text{ K and } 77 \text{ K})$, the functions: σ, μ, μ_H, D , expressed respectively in $\left(\frac{10^3}{\text{ohm}\times\text{cm}}, \frac{10^2 \times \text{cm}^2}{\text{V}\times\text{s}}, \frac{10^2 \times \text{cm}^2}{\text{V}\times\text{s}}, \frac{\text{cm}^2}{\text{s}}\right)$, decrease with increasing r_a .

Acceptor	Ga	Mg	In	Cd
r_a (nm)	0.126	0.140	0.144	0.148

For $x=0$, the values of (σ, μ, μ_H, D) at 4.5 K

$N (10^{19} \text{ cm}^{-3})$				
15	2.54, 1.430, 1.430, 9.79	2.08, 1.307, 1.307, 8.30	2.03, 1.295, 1.295, 8.14	2.01, 1.291, 1.291, 8.09
16	2.72, 1.402, 1.402, 10.2	2.23, 1.278, 1.278, 8.65	2.18, 1.266, 1.266, 8.49	2.17, 1.262, 1.262, 8.44
17	2.89, 1.377, 1.377, 10.5	2.39, 1.252, 1.252, 8.99	2.34, 1.240, 1.240, 8.82	2.32, 1.236, 1.236, 8.77

For $x=0.5$, the values of (σ, μ, μ_H, D) at 4.5 K

$N (10^{19} \text{ cm}^{-3})$				
15	4.07, 1.930, 1.930, 19.1	3.48, 1.723, 1.723, 16.6	3.42, 1.703, 1.703, 16.3	3.40, 1.696, 1.696, 16.2
16	4.31, 1.901, 1.901, 19.8	3.69, 1.695, 1.695, 17.2	3.63, 1.675, 1.675, 16.9	3.61, 1.668, 1.668, 16.8
17	4.56, 1.875, 1.875, 20.4	3.91, 1.670, 1.670, 17.73	3.84, 1.650, 1.650, 17.4	3.82, 1.643, 1.643, 17.3

For $x=1$, the values of (σ, μ, μ_H, D) at 4.5 K

$N (10^{19} \text{ cm}^{-3})$				
15	7.11, 3.095, 3.095, 45.8	6.15, 2.718, 2.718, 39.8	6.06, 2.681, 2.681, 39.2	6.03, 2.668, 2.668, 39.0
16	7.52, 3.060, 3.060, 47.3	6.51, 2.686, 2.686, 41.2	6.41, 2.648, 2.648, 40.6	6.38, 2.636, 2.636, 40.4
17	7.93, 3.029, 3.029, 48.9	6.86, 2.656, 2.656, 42.5	6.76, 2.619, 2.619, 41.9	6.72, 2.606, 2.606, 41.6

For $x=0$, the values of (σ, μ, μ_H, D) at 77K

$N (10^{19} \text{ cm}^{-3})$				
15	2.61, 1.464, 1.542, 9.98	2.13, 1.343, 1.426, 8.48	2.08, 1.332, 1.416, 8.32	2.07, 1.328, 1.413, 8.27
16	2.78, 1.432, 1.500, 10.3	2.29, 1.309, 1.381, 8.82	2.24, 1.297, 1.370, 8.66	2.22, 1.294, 1.366, 8.60
17	2.95, 1.403, 1.464, 10.7	2.44, 1.279, 1.342, 9.14	2.39, 1.267, 1.330, 8.98	2.37, 1.263, 1.326, 8.92

For $x=0.5$, the values of (σ, μ, μ_H, D) at 77K

$N (10^{19} \text{ cm}^{-3})$				
15	4.12, 1.952, 2.002, 19.3	3.56, 1.744, 1.792, 16.7	3.46, 1.724, 1.771, 16.5	3.44, 1.717, 1.764, 16.4
16	4.36, 1.921, 1.966, 19.9	3.73, 1.714, 1.756, 17.3	3.67, 1.693, 1.736, 17.0	3.65, 1.687, 1.729, 16.9

17 4.60, 1.893, 1.934, 20.6 3.95, 1.687, 1.725, 17.9 3.88, 1.666, 1.704, 17.6 3.86, 1.660, 1.697, 17.5

For x=1, the values of (σ, μ, μ_H, D) at 77K

N (10^{19} cm^{-3})

15	7.14, 3.111, 3.147, 46.0	6.19, 2.732, 2.765, 40.0	6.09, 2.695, 2.730, 39.4	6.06, 2.682, 2.714, 39.2
16	7.55, 3.075, 3.107, 47.5	6.54, 2.698, 2.728, 41.3	6.44, 2.661, 2.690, 40.7	6.41, 2.649, 2.677, 40.5
17	7.96, 3.042, 3.072, 49.0	6.89, 2.668, 2.694, 42.6	6.79, 2.630, 2.657, 42.0	6.75, 2.618, 2.644, 41.8

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x$ - alloy, one notes that, for given x, $N > N_{CDP}$ and $T(=4.5 \text{ K and } 77 \text{ K})$, the functions: σ, μ, μ_H, D , expressed respectively in $\left(\frac{10^3}{\text{ohm} \times \text{cm}}, \frac{10^2 \times \text{cm}^2}{\text{V} \times \text{s}}, \frac{10^2 \times \text{cm}^2}{\text{V} \times \text{s}}, \frac{\text{cm}^2}{\text{s}}\right)$, decrease with increasing r_a .

Acceptor	Ga	Mg	In	Cd
r_a (nm)	0.126	0.140	0.144	0.148

For x=0, the values of (σ, μ, μ_H, D) at 4.5 K

N (10^{19} cm^{-3})

15	2.54, 1.430, 1.430, 9.79	2.08, 1.307, 1.307, 8.30	2.03, 1.295, 1.295, 8.14	2.01, 1.291, 1.291, 8.09
16	2.72, 1.402, 1.402, 10.2	2.23, 1.278, 1.278, 8.65	2.18, 1.266, 1.266, 8.49	2.17, 1.262, 1.262, 8.44
17	2.89, 1.377, 1.377, 10.5	2.39, 1.252, 1.252, 8.99	2.34, 1.240, 1.240, 8.82	2.32, 1.236, 1.236, 8.77

For x=0.5, the values of (σ, μ, μ_H, D) at 4.5 K

N (10^{19} cm^{-3})

15	4.07, 1.930, 1.930, 19.1	3.48, 1.723, 1.723, 16.6	3.42, 1.703, 1.703, 16.3	3.40, 1.696, 1.696, 16.2
16	4.31, 1.901, 1.901, 19.8	3.69, 1.695, 1.695, 17.2	3.63, 1.675, 1.675, 16.9	3.61, 1.668, 1.668, 16.8
17	4.56, 1.875, 1.875, 20.4	3.91, 1.670, 1.670, 17.7	3.84, 1.650, 1.650, 17.4	3.82, 1.643, 1.643, 17.3

For x=1, the values of (σ, μ, μ_H, D) at 4.5 K

N (10^{19} cm^{-3})

15	7.11, 3.095, 3.095, 45.8	6.15, 2.718, 2.718, 39.8	6.06, 2.681, 2.681, 39.2	6.03, 2.668, 2.668, 39.0
16	7.52, 3.060, 3.060, 47.3	6.51, 2.686, 2.686, 41.2	6.41, 2.648, 2.648, 40.6	6.38, 2.636, 2.636, 40.4
17	7.93, 3.029, 3.029, 48.9	6.86, 2.656, 2.656, 42.5	6.76, 2.619, 2.619, 41.9	6.72, 2.606, 2.606, 41.6

For x=0, the values of (σ, μ, μ_H, D) at 77K

N (10^{19} cm^{-3})

15	2.61, 1.464, 1.542, 9.98	2.13, 1.343, 1.426, 8.48	2.08, 1.332, 1.416, 8.32	2.07, 1.328, 1.413, 8.27
16	2.78, 1.432, 1.500, 10.3	2.29, 1.309, 1.381, 8.82	2.24, 1.297, 1.370, 8.66	2.22, 1.294, 1.366, 8.60
17	2.95, 1.403, 1.464, 10.7	2.44, 1.279, 1.342, 9.14	2.39, 1.267, 1.330, 8.98	2.37, 1.263, 1.326, 8.92

For x=0.5, the values of (σ, μ, μ_H, D) at 77K

N (10^{19} cm^{-3})

15	4.12, 1.952, 2.002, 19.3	3.52, 1.744, 1.792, 16.7	3.46, 1.724, 1.771, 16.5	3.44, 1.717, 1.764, 16.4
16	4.36, 1.921, 1.966, 19.9	3.74, 1.714, 1.756, 17.3	3.67, 1.693, 1.736, 17.0	3.65, 1.687, 1.729, 16.9
17	4.60, 1.893, 1.934, 20.6	3.65, 1.687, 1.725, 17.9	3.88, 1.666, 1.704, 17.6	3.86, 1.660, 1.697, 17.5

For x=1, the values of (σ, μ, μ_H, D) at 77K

$N (10^{19} \text{ cm}^{-3})$				
15	7.14, 3.111, 3.147, 46.0	6.19, 2.732, 2.765, 40.0	6.09, 2.695, 2.727, 39.4	6.06, 2.682, 2.714, 39.2
16	7.55, 3.075, 3.107, 47.5	6.54, 2.698, 2.728, 41.3	6.44, 2.661, 2.690, 40.7	6.41, 2.649, 2.677, 40.5
17	7.96, 3.042, 3.072, 49.0	6.89, 2.668, 2.694, 42.6	6.79, 2.630, 2.657, 42.0	6.75, 2.618, 2.644, 41.8

Table 4n

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy and for $T=3\text{K}$ and 80K , the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease).

Donor	P	As	Sb	Sn
For $x=0$ and $N=1.3 \times 10^{18} \text{ cm}^{-3}$, one has:				
$\xi_n(T=3\text{K})$ ↘	171.759	170.364	169.200	168.903
$\xi_n(T=80\text{K})$ ↘	6.639	6.588	6.546	6.535
$\kappa_{\text{L}}(T=3\text{K}) \left(\frac{10^{-5} \times W}{\text{cm} \times \text{K}} \right)$ ↘	10.915	9.586	8.773	8.596
$\kappa_{\text{L}}(T=80\text{K}) \left(\frac{10^{-4} \times W}{\text{cm} \times \text{K}} \right)$ ↘	33.231	29.245	26.813	26.282
$-S(T=3\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	3.301	3.328	3.351	3.356
$-S(T=80\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	7.947	7.999	8.044	8.055
$-VC1(T=3\text{K}) \left(\frac{10^{-6} \times V}{\text{K}} \right)$ ↘	2.200	2.218	2.233	2.237
$-VC1(T=80\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	4.292	4.307	4.319	4.322
$-VC2(T=3\text{K}) \left(\frac{10^{-6} \times V}{\text{K}} \right)$ ↘	6.599	6.653	6.699	6.711
$-VC2(T=80\text{K}) \left(\frac{10^{-3} \times V}{\text{K}} \right)$ ↘	3.433	3.445	3.455	3.458
$-Ts(T=3\text{K}) \left(\frac{10^{-6} \times V}{\text{K}} \right)$ ↘	3.300	3.327	3.349	3.355
$-Ts(T=80\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	6.438	6.460	6.479	6.484
$-Pt(T=3\text{K}) (10^{-5} \times V)$ ↘	0.990	0.998	1.005	1.007
$-Pt(T=80\text{K}) (10^{-3} \times V)$ ↘	6.357	6.399	6.435	6.444
$ZT(T=3\text{K}) (10^{-4})$ ↗	4.460	4.533	4.595	4.612
$ZT(T=80\text{K}) (10^{-1})$ ↗	2.585	2.619	2.648	2.656
For $x=0.5$ and $N=2.36 \times 10^{18} \text{ cm}^{-3}$, one has:				
$\xi_n(T=3\text{K})$ ↘	159.155	155.782	152.950	152.226
$\xi_n(T=80\text{K})$ ↘	6.181	6.059	5.956	5.930
$\kappa_{\text{L}}(T=3\text{K}) \left(\frac{10^{-5} \times W}{\text{cm} \times \text{K}} \right)$ ↘	8.202	7.149	6.491	6.346
$\kappa_{\text{L}}(T=80\text{K}) \left(\frac{10^{-4} \times W}{\text{cm} \times \text{K}} \right)$ ↘	25.480	22.343	20.396	19.967
$-S(T=3\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	3.562	3.639	3.706	3.724
$-S(T=80\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	8.445	8.588	8.711	8.743
$-VC1(T=3\text{K}) \left(\frac{10^{-6} \times V}{\text{K}} \right)$ ↘	2.374	2.425	2.470	2.482
$-VC1(T=80\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	4.426	4.462	4.492	4.500
$-VC2(T=3\text{K}) \left(\frac{10^{-6} \times V}{\text{K}} \right)$ ↘	7.121	7.276	7.410	7.445
$-VC2(T=80\text{K}) \left(\frac{10^{-3} \times V}{\text{K}} \right)$ ↘	3.541	3.569	3.593	3.600
$-Ts(T=3\text{K}) \left(\frac{10^{-6} \times V}{\text{K}} \right)$ ↘	3.561	3.638	3.705	3.723
$-Ts(T=80\text{K}) \left(\frac{10^{-5} \times V}{\text{K}} \right)$ ↘	6.639	6.692	6.738	6.749
$-Pt(T=3\text{K}) (10^{-5} \times V)$ ↘	1.069	1.092	1.112	1.117
$-Pt(T=80\text{K}) (10^{-3} \times V)$ ↘	6.756	6.870	6.969	6.995
$ZT(T=3\text{K}) (10^{-4})$ ↗	5.194	5.421	5.624	5.677

$ZT_{(T=30K)}(10^{-1})$	↗	2.919	3.019	3.106	3.129
For $x=1$ and $N=4.1 \times 10^{18} \text{ cm}^{-3}$, one has:					
$\xi_n(T=3K)$	↘	160.495	153.962	148.425	147.001
$\xi_n(T=80K)$	↘	6.230	5.993	5.792	5.740
$\kappa_{(T=3K)}\left(\frac{10^{-5} \times W}{\text{cm} \times K}\right)$	↘	7.114	6.088	5.431	5.283
$\kappa_{(T=80K)}\left(\frac{10^{-4} \times W}{\text{cm} \times K}\right)$	↘	22.048	19.094	17.219	16.801
$-S_{(T=3K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	3.532	3.682	3.819	3.856
$-S_{(T=80K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	8.390	8.667	8.915	8.980
$-VC1_{(T=3K)}\left(\frac{10^{-6} \times V}{K}\right)$	↘	2.354	2.454	2.545	2.570
$-VC1_{(T=80K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	4.412	4.481	4.541	4.557
$-VC2_{(T=3K)}\left(\frac{10^{-6} \times V}{K}\right)$	↘	7.062	7.361	7.636	7.710
$-VC2_{(T=80K)}\left(\frac{10^{-3} \times V}{K}\right)$	↘	3.529	3.585	3.633	3.646
$-Ts_{(T=3K)}\left(\frac{10^{-6} \times V}{K}\right)$	↘	3.531	3.681	3.818	3.855
$-Ts_{(T=80K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	6.617	6.721	6.812	6.835
$-Pt_{(T=3K)}(10^{-5} \times V)$	↘	1.060	1.105	1.146	1.160
$-Pt_{(T=80K)}(10^{-3} \times V)$	↘	6.712	6.933	7.132	7.184
$ZT_{(T=3K)}(10^{-4})$	↗	5.107	5.550	5.972	6.088
$ZT_{(T=80K)}(10^{-1})$	↗	2.881	3.075	3.253	3.301

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x$ -crystalline alloy and for $T=3K$ and $80K$, the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease).

Donor		P	As	Sb	Sn
For $x=0$ and $N=1.3 \times 10^{18} \text{ cm}^{-3}$, one has:					
$\xi_n(T=3K)$	↘	171.759	170.364	169.200	168.903
$\xi_n(T=80K)$	↘	6.639	6.588	6.546	6.535
$\kappa_{(T=3K)}\left(\frac{10^{-5} \times W}{\text{cm} \times K}\right)$	↘	10.915	9.586	8.773	8.596
$\kappa_{(T=80K)}\left(\frac{10^{-4} \times W}{\text{cm} \times K}\right)$	↘	33.231	29.245	26.813	26.282
$-S_{(T=3K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	3.301	3.328	3.351	3.356
$-S_{(T=80K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	7.947	7.999	8.044	8.055
$-VC1_{(T=3K)}\left(\frac{10^{-6} \times V}{K}\right)$	↘	2.200	2.218	2.233	2.237
$-VC1_{(T=80K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	4.292	4.307	4.319	4.322
$-VC2_{(T=3K)}\left(\frac{10^{-6} \times V}{K}\right)$	↘	6.599	6.653	6.699	6.711
$-VC2_{(T=80K)}\left(\frac{10^{-3} \times V}{K}\right)$	↘	3.433	3.445	3.455	3.458
$-Ts_{(T=3K)}\left(\frac{10^{-6} \times V}{K}\right)$	↘	3.300	3.327	3.349	3.355
$-Ts_{(T=80K)}\left(\frac{10^{-5} \times V}{K}\right)$	↘	6.438	6.460	6.479	6.484
$-Pt_{(T=3K)}(10^{-5} \times V)$	↘	0.990	0.998	1.005	1.007
$-Pt_{(T=80K)}(10^{-3} \times V)$	↘	6.357	6.399	6.435	6.444
$ZT_{(T=3K)}(10^{-4})$	↗	4.460	4.533	4.595	4.612
$ZT_{(T=80K)}(10^{-1})$	↗	2.585	2.619	2.648	2.656

For $x=0.5$ and $N=1.5 \times 10^{18} \text{ cm}^{-3}$, one has:

$\xi_n(T=3K)$	↘	174.573	172.997	171.681	171.346
$\xi_n(T=80K)$	↘	6.742	6.684	6.636	6.624

$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{cm \times K} \right) \searrow$	10.844	9.522	8.712	8.536
$\kappa_{(T=80K)} \left(\frac{10^{-4} \times W}{cm \times K} \right) \searrow$	32.883	28.938	26.527	26.000
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.247	3.277	3.302	3.309
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	7.842	7.901	7.950	7.962
$-VC1_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	2.164	2.184	2.201	2.205
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	4.262	4.279	4.293	4.296
$-VC2_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.493	6.552	6.602	6.615
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right) \searrow$	3.409	3.423	3.434	3.437
$-Ts_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.246	3.276	3.301	3.308
$-Ts_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.392	6.418	6.439	6.444
$-Pt_{(T=3K)} (10^{-5} \times V) \searrow$	0.974	0.983	0.991	0.993
$-Pt_{(T=80K)} (10^{-3} \times V) \searrow$	6.274	6.320	6.360	6.370
$ZT_{(T=3K)} (10^{-4}) \nearrow$	4.317	4.396	4.464	4.481
$ZT_{(T=80K)} (10^{-1}) \nearrow$	2.518	2.555	2.587	2.595

For $x=1$ and $N=1.7 \times 10^{18} \text{ cm}^{-3}$, one has:

$\xi_{n(T=3K)} \searrow$	176.194	174.421	172.940	172.563
$\xi_{n(T=80K)} \searrow$	6.801	6.736	6.682	6.668
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{cm \times K} \right) \searrow$	10.697	9.390	8.587	8.412
$\kappa_{(T=80K)} \left(\frac{10^{-4} \times W}{cm \times K} \right) \searrow$	32.368	28.481	26.101	25.581
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.218	3.250	3.278	3.285
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	7.784	7.848	7.903	7.917
$-VC1_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	2.144	2.166	2.185	2.189
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	4.244	4.263	4.279	4.283
$-VC2_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.433	6.499	6.554	6.569
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right) \searrow$	3.395	3.411	3.423	3.427
$-Ts_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.217	3.249	3.277	3.284
$-Ts_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.366	6.395	6.419	6.425
$-Pt_{(T=3K)} (10^{-5} \times V) \searrow$	0.965	0.975	0.983	0.986
$-Pt_{(T=80K)} (10^{-3} \times V) \searrow$	6.227	6.278	6.322	6.333
$ZT_{(T=3K)} (10^{-4}) \nearrow$	4.238	4.325	4.399	4.418
$ZT_{(T=80K)} (10^{-1}) \nearrow$	2.478	2.521	2.556	2.565

Table 4p

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy and for $T=3\text{K}$ and 80K , the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: $\nearrow$ (increase), and $\searrow$ (decrease).

Acceptor	Ga	Mg	In	Cd
For $x=0$ and $N=7 \times 10^{19} \text{ cm}^{-3}$, one has:				
$\xi_{n(T=3K)} \searrow$	170.231	123.368	116.854	114.587
$\xi_{n(T=80K)} \searrow$	6.584	4.871	4.622	4.533
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{cm \times K} \right) \searrow$	7.048	4.301	3.980	3.871

$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{cm \times K} \right)$ ↘	2.150	1.448	1.362	1.332
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	3.330	4.595	4.851	4.947
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	8.004	10.222	10.630	10.782
$-VC1_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	2.219	3.061	3.232	3.296
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	4.308	4.925	5.115	5.198
$-VC2_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	6.659	9.184	9.695	9.887
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right)$ ↘	3.447	3.940	4.092	4.158
$-Ts_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	3.329	4.592	4.848	4.943
$-Ts_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	6.462	7.388	7.673	7.797
$-Pt_{(T=3K)} (10^{-5} \times V)$ ↘	0.999	1.378	1.455	1.484
$-Pt_{(T=80K)} (10^{-3} \times V)$ ↘	6.404	8.178	8.504	8.625
$ZT_{(T=3K)} (10^{-4})$ ↗	4.540	8.642	9.632	10.017
$ZT_{(T=80K)} (10^{-1})$ ↗	2.623	4.227	4.626	4.758

For $x=0.5$ and $N=5 \times 10^{19} \text{ cm}^{-3}$ one has:

$\xi_n(T=3K)$ ↘	172.126	151.067	148.313	147.367
$\xi_n(T=80K)$ ↘	6.653	5.888	5.788	5.754
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{cm \times K} \right)$ ↘	7.089	5.417	5.233	5.172
$\kappa_{(T=80K)} \left(\frac{10^{-5} \times W}{cm \times K} \right)$ ↘	2.157	1.708	1.660	1.643
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	3.294	3.753	3.822	3.847
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	7.933	8.795	8.920	8.964
$-VC1_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	2.195	2.501	2.547	2.563
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	4.288	4.512	4.542	4.553
$-VC2_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	6.585	7.502	7.641	7.691
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right)$ ↘	3.430	3.610	3.634	3.642
$-Ts_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	3.293	3.751	3.821	3.845
$-Ts_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	6.432	6.768	6.813	6.829
$-Pt_{(T=3K)} (10^{-5} \times V)$ ↘	0.988	1.126	1.147	1.154
$-Pt_{(T=80K)} (10^{-3} \times V)$ ↘	6.346	7.036	7.136	7.171
$ZT_{(T=3K)} (10^{-4})$ ↗	4.441	5.764	5.981	6.058
$ZT_{(T=80K)} (10^{-1})$ ↗	2.576	3.166	3.257	3.289

For $x=1$ and $N=3 \times 10^{19} \text{ cm}^{-3}$ one has:

$\xi_n(T=3K)$ ↘	140.573	132.285	131.224	130.860
$\xi_n(T=80K)$ ↘	5.507	5.203	5.164	5.151
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{cm \times K} \right)$ ↘	5.569	4.603	4.499	4.465
$\kappa_{(T=80K)} \left(\frac{10^{-5} \times W}{cm \times K} \right)$ ↘	1.796	1.514	1.484	1.474
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	4.033	4.285	4.320	4.332
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	9.289	9.716	9.774	9.794
$-VC1_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	2.687	2.855	2.878	2.886
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	4.633	4.749	4.767	4.773
$-VC2_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right)$ ↘	8.062	8.566	8.635	8.659

$-VC2_{(T=3K)} \left(\frac{10^{-3} \times V}{K} \right) \searrow$	3.706	3.799	3.813	3.818
$-TS_{(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	4.031	4.283	4.318	4.330
$-TS_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.949	7.124	7.150	7.159
$-Pt_{(T=3K)} (10^{-5} \times V) \searrow$	1.210	1.285	1.296	1.299
$-Pt_{(T=80K)} (10^{-3} \times V) \searrow$	7.431	7.773	7.819	7.835
$ZT_{(T=3K)} (10^{-4}) \nearrow$	6.657	7.517	7.639	7.682
$ZT_{(T=80K)} (10^{-1}) \nearrow$	3.532	3.864	3.910	3.926

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x - \text{alloy}$ and for $T=3K$ and $80K$, the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: $\nearrow$ (increase), and $\searrow$ (decrease).

Acceptor	Ga	Mg	In	Cd
For $x=0$ and $N=7 \times 10^{19} \text{ cm}^{-3}$, one has:				
$\xi_n(T=3K) \searrow$	170.231	123.368	116.854	114.587
$\xi_n(T=80K) \searrow$	6.584	4.871	4.622	4.533
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{\text{cm} \times K} \right) \searrow$	7.048	4.301	3.980	3.871
$\kappa_{(T=80K)} \left(\frac{10^{-3} \times W}{\text{cm} \times K} \right) \searrow$	2.150	1.448	1.362	1.332
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.330	4.595	4.851	4.947
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	8.004	10.222	10.630	10.782
$-VC1_{(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	2.219	3.061	3.232	3.296
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	4.308	4.925	5.115	5.198
$-VC2_{(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	6.659	9.184	9.695	9.887
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right) \searrow$	3.447	3.940	4.092	4.158
$-TS_{(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	3.329	4.592	4.848	4.943
$-TS_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.462	7.388	7.673	7.797
$-Pt_{(T=3K)} (10^{-5} \times V) \searrow$	0.999	1.378	1.455	1.484
$-Pt_{(T=80K)} (10^{-3} \times V) \searrow$	6.404	8.178	8.504	8.625
$ZT_{(T=3K)} (10^{-4}) \nearrow$	4.540	8.642	9.632	10.017
$ZT_{(T=80K)} (10^{-1}) \nearrow$	2.623	4.227	4.626	4.758

For $x=0.5$ and $N=4 \times 10^{19} \text{ cm}^{-3}$ one has:

$\xi_n(T=3K) \searrow$	172.582	141.212	137.021	135.574
$\xi_n(T=80K) \searrow$	6.669	5.530	5.377	5.324
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{\text{cm} \times K} \right) \searrow$	7.384	5.221	4.978	4.896
$\kappa_{(T=80K)} \left(\frac{10^{-3} \times W}{\text{cm} \times K} \right) \searrow$	2.245	1.681	1.619	1.598
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.285	4.014	4.137	4.181
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	7.916	9.257	9.467	9.542
$-VC1_{(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	2.189	2.675	2.757	2.786
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	4.283	4.625	4.679	4.699
$-VC2_{(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	6.568	8.025	8.270	8.359
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right) \searrow$	3.426	3.699	3.743	3.759

$-T_{S(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	3.284	4.013	4.135	4.179
$-T_{S(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.425	6.937	7.019	7.049
$-Pt_{(T=3K)} (10^{-5} \times V) \searrow$	0.985	1.204	1.241	1.254
$-Pt_{(T=80K)} (10^{-3} \times V) \searrow$	6.333	7.406	7.574	7.634
$ZT_{(T=3K)} (10^{-4}) \nearrow$	4.417	6.597	7.007	7.157
$ZT_{(T=80K)} (10^{-1}) \nearrow$	2.565	3.507	3.669	3.727

For $x=1$ and $N=2 \times 10^{19} \text{ cm}^{-3}$ one has:

$\xi_n(T=3K) \searrow$	176.517	158.106	155.713	154.892
$\xi_n(T=80K) \searrow$	6.812	6.143	6.057	6.027
$\kappa_{(T=3K)} \left(\frac{10^{-5} \times W}{\text{cm} \times K} \right) \searrow$	7.912	6.215	6.031	5.970
$\kappa_{(T=80K)} \left(\frac{10^{-5} \times W}{\text{cm} \times K} \right) \searrow$	2.393	1.934	1.885	1.869
$-S_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	3.212	3.585	3.641	3.660
$-S_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	7.772	8.489	8.591	8.626
$-VC1_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	2.140	2.389	2.426	2.439
$-VC1_{(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	4.241	4.437	4.462	4.471
$-VC2_{(T=3K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.422	7.169	7.279	7.317
$-VC2_{(T=80K)} \left(\frac{10^{-3} \times V}{K} \right) \searrow$	3.393	3.549	3.570	3.577
$-T_{S(T=3K)} \left(\frac{10^{-6} \times V}{K} \right) \searrow$	3.211	3.584	3.639	3.659
$-T_{S(T=80K)} \left(\frac{10^{-5} \times V}{K} \right) \searrow$	6.361	6.655	6.693	6.707
$-Pt_{(T=3K)} (10^{-5} \times V) \searrow$	0.963	1.076	1.092	1.098
$-Pt_{(T=80K)} (10^{-3} \times V) \searrow$	6.217	6.791	6.873	6.901
$ZT_{(T=3K)} (10^{-4}) \nearrow$	4.222	5.263	5.426	5.483
$ZT_{(T=80K)} (10^{-1}) \nearrow$	2.472	2.950	3.021	3.046

Table 5n:

In the $\mathbf{X(x)} \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy, for a given N and with increasing T , the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: $\nearrow$, decrease: $\searrow$). One notes here that with increasing T : (i) for $\xi_n \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{\min.} (\approx -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{\max.} = 1$, (ii) for $\xi_n = 1$, those of S , ZT , $(ZT)_{\text{Mott}}$, $VC1$, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$, respectively, and (iii) for $\xi_n \approx 1.8138$, $(ZT)_{\text{Mott}} = 1$.

For $x=0$,

In the degenerate P- $\mathbf{Y(x)}$ - alloy, for $N = 2 \times N_{\text{cdn}}(r_p) = 1.1086356 \times 10^{17} \text{ cm}^{-3}$, one gets:

$T(K) \nearrow$	28.56082	29.1832614	29.81117	39.71148	39.75222
$\xi_n \searrow$	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K} \right) \searrow$	-1.562	-1.563	$\nearrow$	-1.322	$\nearrow$
$ZT \nearrow$	0.999	1	$\searrow$	0.715	$\searrow$
$(ZT)_{\text{Mott}} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K} \right) \nearrow$	-0.061	0	$\nearrow$	1.105	$\nearrow$
$VC2 \left(10^{-4} \frac{V}{K} \right) \nearrow$	-1.752	0	$\nearrow$	43.879	$\nearrow$
$T_s \left(10^{-4} \frac{V}{K} \right) \nearrow$	-0.092	0	$\nearrow$	1.657	$\nearrow$
$Pt (10^{-3} V) \searrow$	-4.4612	-4.5613	$\searrow$	-5.2487	$\searrow$

In the degenerate As- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{As}) = 1.4113061 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	↗	33.5474		34.278521		35.01605		46.644917		46.69277
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mott}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-2.058	↗	0	↗	2.203	↗	51.540	↗	51.785
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-5.2401	↘	-5.3577	↘	-5.4695	↘	-6.1651	↗	-6.1634

In the degenerate Sb- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sb}) = 1.6628902 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	↗	37.4243		38.239921		39.0627		52.035441		52.08883
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mott}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-2.296	↗	0	↗	2.458	↗	57.496	↗	57.769
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-5.8457	↘	-5.9769	↘	-6.1016	↘	-6.8775	↗	-6.8757

In the degenerate Sn- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sn}) = 1.7268353 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	↗	38.3777		39.214066		40.0578		53.361021		53.41577
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mott}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-2.354	↗	0	↗	2.520	↗	58.961	↗	59.241
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-5.9946	↘	-6.1291	↘	-6.2570	↘	-7.0527	↗	-7.0509

For $x=0.5$,

In the degenerate P- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_p) = 4.8999962 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	↗	50.051		51.14178		52.24212		69.591804		69.6632
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mott}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-3.070	↗	0	↗	3.287	↗	76.895	↗	77.260
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-7.8180	↘	-7.9934	↘	-8.1602	↘	-9.1980	↗	-9.1955

In the degenerate As- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{As}) = 6.2377524 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	58.7897	60.070894	61.36329	81.742205	81.826
ξ_n	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-4} \frac{V}{K})$	-3.606	0	3.861	90.321	90.749
$T_s(10^{-4} \frac{V}{K})$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-9.1829	-9.3891	-9.5848	-10.8039	-10.8010

In the degenerate Sb- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sb}) = 7.349715 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	65.5837	67.012993	68.4548	91.18875	91.28231
ξ_n	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-4} \frac{V}{K})$	-4.023	0	4.307	100.758	101.237
$T_s(10^{-4} \frac{V}{K})$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-10.2442	-10.4741	-10.6926	-12.0524	-12.0496

In the degenerate Sn- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sn}) = 7.6323424 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	67.2544	68.72012	70.1987	93.511745	93.60769
ξ_n	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-4} \frac{V}{K})$	-4.125	0	4.417	103.325	103.816
$T_s(10^{-4} \frac{V}{K})$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-10.5051	-10.7409	-10.9650	-12.3595	-12.3562

For $x=1$,

In the degenerate P- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_p) = 1.4861586 \times 10^{18} \text{ cm}^{-2}$, one gets:

T(K)	77.7223	79.416135	81.1248	108.06648	108.17735
ξ_n	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-4} \frac{V}{K})$	-4.767	0	5.104	119.407	119.974
$T_s(10^{-4} \frac{V}{K})$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-12.1402	-12.4127	-12.6717	-14.2832	-14.2794

In the degenerate As- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{As}) = 1.8918973 \times 10^{18} \text{ cm}^{-3}$, one gets:

T(K)	↗	91.2923	93.28182	95.288	126.93438	127.0646
ξ_n	↘	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘ -1.563 ↗	-1.562	↗ -1.322 ↗	-1.320
ZT		0.999	↗ 1 ↘	0.999	↘ 0.715 ↘	0.713
$(ZT)_{Mott}$	↗	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗ 0 ↗	0.063	↗ 1.105 ↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-5.600	↗ 0 ↗	5.993	↗ 140.255 ↗	140.921
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗ 0 ↗	0.094	↗ 1.657 ↗	1.663
Pt($10^{-3}V$)		-14.2598	↘ -14.5799 ↘	-14.8840	↘ -16.7769 ↗	-16.7725

In the degenerate Sb- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sb}) = 2.2291532 \times 10^{18} \text{ cm}^{-3}$, one gets:

T(K)	↗	101.8425	104.06194	106.3009	141.60356	141.7488
ξ_n	↘	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘ -1.563 ↗	-1.562	↗ -1.322 ↗	-1.320
ZT		0.999	↗ 1 ↘	0.999	↘ 0.715 ↘	0.713
$(ZT)_{Mott}$	↗	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗ 0 ↗	0.063	↗ 1.105 ↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-6.247	↗ 0 ↗	6.688	↗ 156.464 ↗	157.207
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗ 0 ↗	0.094	↗ 1.657 ↗	1.663
Pt($10^{-3}V$)		-15.9078	↘ -16.2649 ↘	-16.6042	↘ -18.7158 ↗	-18.7108

In the degenerate Sn- $X(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sn}) = 2.3148734 \times 10^{18} \text{ cm}^{-3}$, one gets:

T(K)	↗	104.4368	106.71287	109.0089	145.21085	145.3598
ξ_n	↘	1.880	1.8138	1.750	1	0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘ -1.563 ↗	-1.562	↗ -1.322 ↗	-1.320
ZT		0.999	↗ 1 ↘	0.999	↘ 0.715 ↘	0.713
$(ZT)_{Mott}$	↗	0.931	1	1.074	3.290	3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗ 0 ↗	0.063	↗ 1.105 ↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-6.406	↗ 0 ↗	6.859	↗ 160.450 ↗	161.212
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗ 0 ↗	0.094	↗ 1.657 ↗	1.663
Pt($10^{-3}V$)		-16.3130	↘ -16.6792 ↘	-17.0272	↘ -19.1925 ↗	-19.1875

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x$ -crystalline alloy, for a given N and with increasing T , the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T : (i) for $\xi_n \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{\min.} (\approx -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{\max.} = 1$, (ii) for $\xi_n = 1$, those of S , ZT , $(ZT)_{Mott}$, $VC1$, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$ respectively, and (iii) for $\xi_n \approx 1.8138$, $(ZT)_{Mott} = 1$.

For $x=0$,

In the degenerate P- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_P) = 1.1086356 \times 10^{17} \text{ cm}^{-3}$, one gets:

T(K)	↗	28.56082	29.1832614	29.81117	39.71148	39.75222
ξ_n	↘	1.880	1.8138	1.750	1	0.998

$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931 ↗	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-1.752 ↗	0 ↗	1.876 ↗	43.879 ↗	44.087
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-4.4612 ↘	-4.5613 ↘	-4.6565 ↘	-5.2487 ↗	-5.2473

In the degenerate As- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{As}) = 1.4113061 \times 10^{17} \text{ cm}^{-3}$, one gets:

T(K)	↗	33.5474	34.278521	35.01605	46.644917	46.69277
ξ_n	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	↘	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	↗	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931 ↗	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	↗	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	↗	-2.058 ↗	0 ↗	2.203 ↗	51.540 ↗	51.785
$T_s \left(10^{-4} \frac{V}{K}\right)$	↗	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	↘	-5.2401 ↘	-5.3577 ↘	-5.4695 ↘	-6.1651 ↗	-6.1634

In the degenerate Sb- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sb}) = 1.6628902 \times 10^{17} \text{ cm}^{-3}$, one gets:

T(K)	↗	37.4243	38.239921	39.0627	52.035441	52.08883
ξ_n	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	↘	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	↗	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931 ↗	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	↗	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	↗	-2.296 ↗	0 ↗	2.458 ↗	57.496 ↗	57.769
$T_s \left(10^{-4} \frac{V}{K}\right)$	↗	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	↘	-5.8457 ↘	-5.9769 ↘	-6.1016 ↘	-6.8775 ↗	-6.8757

In the degenerate Sn- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_{Sn}) = 1.7268353 \times 10^{17} \text{ cm}^{-3}$, one gets:

T(K)	↗	38.3777	39.214066	40.0578	53.361021	53.41577
ξ_n	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	↘	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	↗	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931 ↗	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	↗	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	↗	-2.354 ↗	0 ↗	2.520 ↗	58.961 ↗	59.241
$T_s \left(10^{-4} \frac{V}{K}\right)$	↗	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	↘	-5.9946 ↘	-6.1291 ↘	-6.2570 ↘	-7.0527 ↗	-7.0509

For $x=0.5$,

In the degenerate P- $Y(x)$ – alloy, for $N = 2 \times N_{CDn}(r_P) = 1.4150071 \times 10^{17} \text{ cm}^{-3}$, one gets:

T(K)	↗	31.14705	31.825855	32.5106	43.307423	43.351855
------	---	----------	------------------	---------	------------------	-----------

ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-1.910	0	2.045	47.852	48.079
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-4.8652	-4.9744	-5.0781	-5.7239	-5.7224

In the degenerate As- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_{As}) = 1.8013205 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	36.5852	37.382499	38.1868	50.868694	50.920886
ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.244	0	2.403	56.207	56.474
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-5.7146	-5.8429	-5.9648	-6.7233	-6.7215

In the degenerate Sb- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_{Sb}) = 2.12243 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	40.8132	41.702611	42.59986	56.74734	56.805563
ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.503	0	2.680	62.703	63.000
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-6.3750	-6.5181	-6.6541	-7.5003	-7.4983

In the degenerate Sn- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_{Sn}) = 2.2040462 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	41.8529	42.764966	43.6851	58.192953	58.252657
ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.567	0	2.749	64.300	64.605
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-6.5374	-6.6841	-6.8236	-7.6914	-7.6893

For x=1,

In the degenerate P- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_P) = 1.7773443 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	33.7876	34.523903	35.2667	46.978824	47.02701
------	---------	------------------	---------	------------------	----------

ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.072	0	2.219	51.909	52.155
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-5.2776	-5.3961	-5.5086	-6.2092	-6.2076

In the degenerate As- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_{As}) = 2.26258 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	39.6867	40.551614	41.4241	55.181106	55.23772
ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.434	0	2.606	60.972	61.262
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-6.1991	-6.3382	-6.4704	-7.2933	-7.2914

In the degenerate Sb- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_{Sb}) = 2.665915 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	44.2731	45.237963	46.2113	61.558113	61.62127
ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.716	0	2.907	68.018	68.341
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-6.9154	-7.0707	-7.2182	-8.1361	-8.1340

In the degenerate Sn- Y(x) – alloy, for $N = 2 \times N_{CDn}(r_{Sn}) = 2.7684306 \times 10^{17} \text{ cm}^{-2}$, one gets:

T(K)	45.40093	46.390382	47.3885	63.12628	63.19104
ξ_m	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.785	0	2.982	69.751	70.082
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-3}V$)	-7.0916	-7.2508	-7.4021	-8.3434	-8.3412

Table 5p:

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ -crystalline alloy, for a given N and with increasing T , the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: $\nearrow$, decrease: $\searrow$). One notes here that with increasing T : (i) for $\xi_p \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{\min.} (\approx -1.563 \times 10^{-4} \frac{\text{V}}{\text{K}})$, those of ZT show a same maximum $(ZT)_{\max.} = 1$, (ii) for $\xi_p = 1$, those of S , ZT , $(ZT)_{\text{Mott}}$, VC1 , and T_s present the same results: $-1.322 \times 10^{-4} \frac{\text{V}}{\text{K}}$, 0.715, 3.290, $1.105 \times 10^{-4} \frac{\text{V}}{\text{K}}$, and $1.657 \times 10^{-4} \frac{\text{V}}{\text{K}}$ respectively, and (iii) for $\xi_p \approx 1.8138$, $(ZT)_{\text{Mott}} = 1$.

For $x=0$,

In the degenerate Ga- $X(x)$ – alloy, for $N = 2 \times N_{\text{CdP}} (r_{\text{Ga}}) = 7.7718202 \times 10^{23} \text{ cm}^{-3}$, one gets:

$T(\text{K})$	$\nearrow$	261.1179	266.80841	272.549	363.06281	363.4353
ξ_p	$\searrow$	1.880	1.8138	1.750	1	0.998
$S (10^{-4} \frac{\text{V}}{\text{K}})$		-1.562	$\searrow$ -1.563 $\nearrow$	-1.562	$\nearrow$ -1.322 $\nearrow$	-1.320
ZT		0.999	$\nearrow$ 1 $\searrow$	0.998	$\searrow$ 0.715 $\searrow$	0.713
$(ZT)_{\text{Mott}}$	$\nearrow$	0.931	1	1.074	3.290	3.306
$\text{VC1} (10^{-4} \frac{\text{V}}{\text{K}})$		-0.061	$\nearrow$ 0 $\nearrow$	0.063	$\nearrow$ 1.105 $\nearrow$	1.109
$\text{VC2} (10^{-2} \frac{\text{V}}{\text{K}})$		-0.160	$\nearrow$ 0 $\nearrow$	0.171	$\nearrow$ 4.012 $\nearrow$	4.030
$T_s (10^{-4} \frac{\text{V}}{\text{K}})$		-0.092	$\nearrow$ 0 $\nearrow$	0.094	$\nearrow$ 1.657 $\nearrow$	1.663
$\text{Pt} (10^{-2} \text{V})$		-4.0787	$\searrow$ -4.1702 $\searrow$	-4.2572	$\searrow$ -4.7986 $\nearrow$	-4.7973

In the degenerate Mg- $X(x)$ – alloy, for $N = 2 \times N_{\text{CdP}} (r_{\text{Mg}}) = 1.015775 \times 10^{23} \text{ cm}^{-3}$, one gets:

$T(\text{K})$	$\nearrow$	312.1424	318.94516	325.8076	434.00854	434.4538
ξ_p	$\searrow$	1.880	1.8138	1.750	1	0.998
$S (10^{-4} \frac{\text{V}}{\text{K}})$		-1.562	$\searrow$ -1.563 $\nearrow$	-1.562	$\nearrow$ -1.322 $\nearrow$	-1.320
ZT		0.999	$\nearrow$ 1 $\searrow$	0.998	$\searrow$ 0.715 $\searrow$	0.713
$(ZT)_{\text{Mott}}$	$\nearrow$	0.931	1	1.074	3.290	3.306
$\text{VC1} (10^{-4} \frac{\text{V}}{\text{K}})$		-0.061	$\nearrow$ 0 $\nearrow$	0.063	$\nearrow$ 1.105 $\nearrow$	1.109
$\text{VC2} (10^{-2} \frac{\text{V}}{\text{K}})$		-0.191	$\nearrow$ 0 $\nearrow$	0.205	$\nearrow$ 4.795 $\nearrow$	4.818
$T_s (10^{-4} \frac{\text{V}}{\text{K}})$		-0.092	$\nearrow$ 0 $\nearrow$	0.094	$\nearrow$ 1.657 $\nearrow$	1.663
$\text{Pt} (10^{-2} \text{V})$		-4.8757	$\searrow$ -4.9851 $\searrow$	-5.0891	$\searrow$ -5.7363 $\nearrow$	-5.7348

In the degenerate In- $X(x)$ – alloy, for $N = 2 \times N_{\text{CdP}} (r_{\text{In}}) = 1.0458077 \times 10^{23} \text{ cm}^{-3}$, one gets:

$T(\text{K})$	$\nearrow$	318.2652	325.20128	332.198	442.52162	442.9756
ξ_p	$\searrow$	1.880	1.8138	1.750	1	0.998
$S (10^{-4} \frac{\text{V}}{\text{K}})$		-1.562	$\searrow$ -1.563 $\nearrow$	-1.562	$\nearrow$ -1.322 $\nearrow$	-1.320
ZT		0.999	$\nearrow$ 1 $\searrow$	0.998	$\searrow$ 0.715 $\searrow$	0.713
$(ZT)_{\text{Mott}}$	$\nearrow$	0.931	1	1.074	3.290	3.306
$\text{VC1} (10^{-4} \frac{\text{V}}{\text{K}})$		-0.061	$\nearrow$ 0 $\nearrow$	0.063	$\nearrow$ 1.105 $\nearrow$	1.109
$\text{VC2} (10^{-2} \frac{\text{V}}{\text{K}})$		-0.195	$\nearrow$ 0 $\nearrow$	0.209	$\nearrow$ 4.890 $\nearrow$	4.913
$T_s (10^{-4} \frac{\text{V}}{\text{K}})$		-0.092	$\nearrow$ 0 $\nearrow$	0.094	$\nearrow$ 1.657 $\nearrow$	1.663
$\text{Pt} (10^{-2} \text{V})$		-4.9713	$\searrow$ -5.0829 $\searrow$	-5.1889	$\searrow$ -5.8488 $\nearrow$	-5.8473

In the degenerate Cd- $X(x)$ – alloy, for $N = 2 \times N_{\text{CdP}} (r_{\text{Cd}}) = 1.0560657 \times 10^{23} \text{ cm}^{-3}$, one gets:

$T(\text{K})$	$\nearrow$	320.343	327.32434	334.367	445.41062	445.8676
---------------	------------	---------	------------------	---------	------------------	----------

ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.998	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.196	0	0.210	4.921	4.945
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-2}V$)	-5.0037	-5.1161	-5.2228	-5.8870	-5.8854

For $x=0.5$,

In the degenerate Ga- $X(x)$ – alloy, for $N = 2 \times N_{Cd_p}(r_{Ga}) = 3.6675104 \times 10^{19} \text{ cm}^{-3}$, one gets:

T(K)	204.384	208.836003	213.329	284.1761	284.467
ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.998	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.125	0	0.134	3.140	3.155
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-2}V$)	-3.1925	-3.2641	-3.3322	-3.7560	-3.7550

In the degenerate Mg- $X(x)$ – alloy, for $N = 2 \times N_{Cd_p}(r_{Mg}) = 4.793427 \times 10^{19} \text{ cm}^{-3}$, one gets:

T(K)	244.32	249.64443	255.016	339.70673	340.0551
ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.998	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.150	0	0.160	3.753	3.771
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-2}V$)	-3.8162	-3.9019	-3.9833	-4.4899	-4.4887

In the degenerate In- $X(x)$ – alloy, for $N = 2 \times N_{Cd_p}(r_{In}) = 4.9351512 \times 10^{19} \text{ cm}^{-3}$, one gets:

T(K)	249.1123	254.54122	260.015	346.37009	346.7254
ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.998	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.153	0	0.163	3.827	3.845
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
Pt ($10^{-2}V$)	-3.8911	-3.9785	-4.0614	-4.5780	-4.5768

In the degenerate Cd- $X(x)$ – alloy, for $N = 2 \times N_{Cd_p}(r_{Cd}) = 4.9835584 \times 10^{19} \text{ cm}^{-3}$, one gets:

T(K)	250.739	256.20298	261.715	384.6313	348.989
------	---------	------------------	---------	-----------------	---------

ξ_p	↘	1.880		1.8138		1.750		1		0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.998	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.154	↗	0	↗	0.165	↗	3.852	↗	3.870
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-2}V$)		-3.9165	↘	-4.0044	↘	-4.0880	↘	-4.6079	↗	-4.6066

For x=1,

In the degenerate Ga- X(x) – alloy, for $N = 2 \times N_{CDP}(r_{Ga}) = 1.3264601 \times 10^{19} \text{ cm}^{-2}$, one gets:

T(K)	↗	146.404		149.59434		152.813		203.56233		203.7711
ξ_p	↘	1.880		1.8138		1.750		1		0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.998	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.125	↗	0	↗	0.096	↗	2.249	↗	2.260
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.090	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-2}V$)		-2.2868	↘	-2.3381	↘	-2.3869	↘	-2.6905	↗	-2.6898

In the degenerate Mg- X(x) – alloy, for $N = 2 \times N_{CDP}(r_{Mg}) = 1.7336801 \times 10^{19} \text{ cm}^{-2}$, one gets:

T(K)	↗	175.0125		178.826413		182.674		243.34024		243.5899
ξ_p	↘	1.880		1.8138		1.750		1		0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.998	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.107	↗	0	↗	0.115	↗	2.689	↗	2.701
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.090	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-2}V$)		-2.7337	↘	-2.7950	↘	-2.8534	↘	-3.2162	↗	-3.2154

In the degenerate In- X(x) – alloy, for $N = 2 \times N_{CDP}(r_{In}) = 1.7849387 \times 10^{19} \text{ cm}^{-2}$, one gets:

T(K)	↗	178.4454		182.3341		186.257		248.11336		248.3679
ξ_p	↘	1.880		1.8138		1.750		1		0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.998	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.109	↗	0	↗	0.117	↗	2.741	↗	2.754
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.090	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-2}V$)		-2.7873	↘	-2.8499	↘	-2.9093	↘	-3.2793	↗	-3.2784

In the degenerate Cd- X(x) – alloy, for $N = 2 \times N_{CDP}(r_{Cd}) = 1.8024466 \times 10^{19} \text{ cm}^{-2}$, one gets:

T(K)	↗	179.6101		183.52446		187.473		249.73316		249.989
ξ_p	↘	1.880		1.8138		1.750		1		0.998

$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.110 ↗	0 ↗	0.118 ↗	2.759 ↗	2.772
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.090 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-2.8055 ↘	-2.8685 ↘	-2.9283 ↘	-3.3007 ↗	-3.2999

In the $Y(x) \equiv CdTe_{1-x}Se_x$ - alloy, for a given N and with increasing T , the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T : (i) for $\xi_p \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.} (\simeq -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_p = 1$, those of S , ZT , $(ZT)_{Mott}$, $VC1$, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$ respectively, and (iii) for $\xi_p \simeq 1.8138$, $(ZT)_{Mott} = 1$.

For $x=0$,

In the degenerate Ga- $Y(x)$ - alloy, for $N = 2 \times N_{CdP} (r_{Ga}) = 7.7718202 \times 10^{23} cm^{-3}$, one gets:

T(K) ↗	261.1179	266.80841	272.549	363.06281	363.4353
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.160 ↗	0 ↗	0.171 ↗	4.012 ↗	4.030
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-4.0787 ↘	-4.1702 ↘	-4.2572 ↘	-4.7986 ↗	-4.7973

In the degenerate Mg- $Y(x)$ - alloy, for $N = 2 \times N_{CdP} (r_{Mg}) = 1.015775 \times 10^{23} cm^{-3}$, one gets:

T(K) ↗	312.1424	318.94516	325.8076	434.00854	434.4538
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.191 ↗	0 ↗	0.205 ↗	4.795 ↗	4.818
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-4.8757 ↘	-4.9851 ↘	-5.0891 ↘	-5.7363 ↗	-5.7348

In the degenerate In- $Y(x)$ - alloy, for $N = 2 \times N_{CdP} (r_{In}) = 1.0458077 \times 10^{23} cm^{-3}$, one gets:

T(K) ↗	318.2652	325.20128	332.198	442.52162	442.9756
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.195 ↗	0 ↗	0.209 ↗	4.890 ↗	4.913

$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-4.9713 ↘	-5.0829 ↘	-5.1889 ↘	-5.8488 ↗	-5.8473

In the degenerate Cd- Y(x) – alloy, for $N = 2 \times N_{Cd} (r_{Cd}) = 1.0560657 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	320.343	327.32434	334.367	445.41062	445.8676
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$		-0.196 ↗	0 ↗	0.210 ↗	4.921 ↗	4.945
$T_s \left(10^{-4} \frac{V}{K}\right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)		-5.0037 ↘	-5.1161 ↘	-5.2228 ↘	-5.8870 ↗	-5.8854

For x=0.5,

In the degenerate Ga- Y(x) – alloy, for $N = 2 \times N_{Ga} (r_{Ga}) = 3.6675104 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	204.3819	208.836008	213.3293	284.17616	284.4677
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$		-0.125 ↗	0 ↗	0.134 ↗	3.140 ↗	3.155
$T_s \left(10^{-4} \frac{V}{K}\right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)		-3.1924 ↘	-3.2641 ↘	-3.3322 ↘	-3.7560 ↗	-3.7550

In the degenerate Mg- Y(x) – alloy, for $N = 2 \times N_{Mg} (r_{Mg}) = 4.793427 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	244.32	249.64443	255.0158	339.70672	340.0552
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$		-0.150 ↗	0 ↗	0.160 ↗	3.753 ↗	3.771
$T_s \left(10^{-4} \frac{V}{K}\right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)		-3.8163 ↘	-3.9019 ↘	-3.9833 ↘	-4.4899 ↗	-4.4887

In the degenerate In- Y(x) – alloy, for $N = 2 \times N_{In} (r_{In}) = 4.9351512 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	249.1122	254.54122	260.018	346.37008	346.7254
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$		-0.153 ↗	0 ↗	0.164 ↗	3.827 ↗	3.845
$T_s \left(10^{-4} \frac{V}{K}\right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663

Pt ($10^{-2}V$) -3.8911 ↘ -3.9785 ↘ -4.0615 ↘ -4.5780 ↗ -4.5768

In the degenerate Cd- Y(x) – alloy, for $N = 2 \times N_{Cd} (r_{Cd}) = 4.9835584 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	250.7385	256.20298	261.7153	348.63135	248.98904
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.154 ↗	0 ↗	0.165 ↗	3.852 ↗	3.870
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)		-3.9165 ↘	-4.0044 ↘	-4.0880 ↘	-4.6079 ↗	-4.6066

For x=1,

In the degenerate Ga- Y(x) – alloy, for $N = 2 \times N_{Ga} (r_{Ga}) = 1.3264601 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	146.4037	149.59434	152.813	203.56233	203.7712
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.090 ↗	0 ↗	0.096 ↗	2.249 ↗	2.260
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)		-2.2868 ↘	-2.3381 ↘	-2.3869 ↘	-2.6905 ↗	-2.6898

In the degenerate Mg- Y(x) – alloy, for $N = 2 \times N_{Mg} (r_{Mg}) = 1.7336801 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	175.0123	178.82641	182.674	243.34024	243.589
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.107 ↗	0 ↗	0.115 ↗	2.689 ↗	2.701
$T_s \left(10^{-4} \frac{V}{K} \right)$		-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)		-2.7337 ↘	-2.7950 ↘	-2.8534 ↘	-3.2162 ↗	-3.2154

In the degenerate In- Y(x) – alloy, for $N = 2 \times N_{In} (r_{In}) = 1.7849387 \times 10^{23} \text{ cm}^{-3}$, one gets:

T(K)	↗	178.445	182.3341	186.257	248.11336	248.367
ξ_p	↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K} \right)$		-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT		0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K} \right)$		-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K} \right)$		-0.109 ↗	0 ↗	0.117 ↗	2.741 ↗	2.754

$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-2.7873 ↘	-2.8500 ↘	-2.9093 ↘	-3.2793 ↗	-3.2784

In the degenerate Cd- $Y(x)$ – alloy, for $N = 2 \times N_{Cd_2} (r_{in}) = 1.8024466 \times 10^{27} \text{ cm}^{-3}$, one gets:

$T(K)$ ↗	179.610	183.52446	187.473	249.73316	249.989
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.998 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-2} \frac{V}{K}\right)$	-0.110 ↗	0 ↗	0.118 ↗	2.759 ↗	2.772
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-2.8055 ↘	-2.8685 ↘	-2.9283 ↘	-3.3007 ↗	-3.2999

Table 6n:

In the $X(x) \equiv \text{CdTe}_{1-x}\text{S}_x$ –crystalline alloy, for a given T and with decreasing N , the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T : (i) for $\xi_n \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{\min.} (\approx -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{\max.} = 1$, (ii) for $\xi_n = 1$, those of S , ZT , $(ZT)_{Mott}$, $VC1$, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $-1.105 \times 10^{-4} \frac{V}{K}$ and $1.657 \times 10^{-4} \frac{V}{K}$ respectively, and (iii) for $\xi_n \approx 1.8138$, $(ZT)_{Mott} = 1$.

For $x=0$,

In the degenerate P- $X(x)$ – alloy, for $T= 29.1832614 \text{ K}$, one gets:

$N(10^{27} \text{ cm}^{-3})$ ↘	1.126855	1.1086356	1.091215	0.90352685	0.902991
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-1.790 ↗	0 ↗	1.836 ↗	32.246 ↗	32.366
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-3}V)$	-4.5584 ↘	-4.5613 ↗	-4.5584 ↗	-3.8571 ↗	-3.8522

In the degenerate As- $X(x)$ – alloy, for $T= 34.278521 \text{ K}$, one gets:

$N(10^{27} \text{ cm}^{-3})$ ↘	1.434499	1.4113061	1.38913	1.1502002	1.149517
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.103 ↗	0 ↗	2.157 ↗	37.876 ↗	38.017
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-3}V)$	-5.3543 ↘	-5.3577 ↗	-5.3543 ↗	-4.5306 ↗	-4.5248

In the degenerate Sb- $X(x)$ – alloy, for $T= 38.239921$ K, one gets:

$N(10^{27} \text{cm}^{-3})$	↘	1.690219		1.6628902		1.63677		1.3552387		1.354434
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-2.346	↗	0	↗	2.405	↗	42.253	↗	42.410
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-5.9731	↘	-5.9769	↗	-5.9731	↗	-5.0542	↗	-5.0477

In the degenerate Sn- $X(x)$ – alloy, for $T=39.214066$ K, one gets:

$N(10^{27} \text{cm}^{-3})$	↘	1.755214		1.7268353		1.6997		1.407353		1.40652
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-2.405	↗	0	↗	2.467	↗	43.329	↗	43.490
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-6.1252	↘	-6.1291	↗	-6.1252	↗	-5.1829	↗	-5.1763

For $x=0.5$,

In the degenerate P- $X(x)$ – alloy, for $T=51.14178$ K, one gets:

$N(10^{27} \text{cm}^{-3})$	↘	4.98052		4.8999962		4.823		3.9934474		3.991075
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-3.137	↗	0	↗	3.218	↗	56.509	↗	56.719
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-7.9883	↘	-7.9934	↗	-7.9883	↗	-6.7594	↗	-6.7507

In the degenerate As- $X(x)$ – alloy, for $T= 60.070894$ K, one gets:

$N(10^{27} \text{cm}^{-3})$	↘	6.34026		6.2377524		6.13974		5.0837051		5.08069
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4} \frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4} \frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4} \frac{V}{K})$		-3.685	↗	0	↗	3.779	↗	66.375	↗	66.621
$T_s(10^{-4} \frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-9.3831	↘	-9.3891	↗	-9.3831	↗	-7.9396	↗	-7.9294

In the degenerate Sb- $X(x)$ – alloy, for $T=67.012993$ K, one gets:

$N(10^{27}cm^{-3})$	↘	7.4705		7.349715		7.2343		5.9899435		5.98639
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-4.111	↗	0	↗	4.213	↗	74.046	↗	74.321
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-10.4674	↘	-10.4741	↗	-10.4674	↗	-8.8571	↗	-8.8457

In the degenerate Sn- $X(x)$ – alloy, for $T=68.72012$ K one gets:

$N(10^{27}cm^{-3})$	↘	7.75777		7.6323424		7.51242		6.2202819		6.21659
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-4.215	↗	0	↗	4.323	↗	75.932	↗	76.214
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-10.7341	↘	-10.7409	↗	-10.7341	↗	-9.0827	↗	-9.0711

For $x=1$,

In the degenerate P- $X(x)$ – alloy, for $T=79.416135$ K, one gets:

$N(10^{27}cm^{-3})$	↘	1.51058		1.4861586		1.46286		1.2112043		1.210485
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-4.871	↗	0	↗	4.985	↗	87.750	↗	88.077
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-12.4048	↘	-12.4127	↗	-12.4048	↗	-10.4964	↗	-10.4829

In the degenerate As- $X(x)$ – alloy, for $T=93.28182$ K, one gets:

$N(10^{27}cm^{-3})$	↘	1.922986		1.8918973		1.86219		1.5418772		1.540962
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{Mett}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-5.721	↗	0	↗	5.865	↗	103.071	↗	103.454
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-14.5706	↘	-14.5799	↗	-14.5706	↗	-12.3291	↗	-12.3132

In the degenerate Sb- $X(x)$ – alloy, for $T=104.06194$ K, one gets:

$N(10^{22}\text{cm}^{-3})$	↘	2.26578		2.2291532		2.1942		1.8167373		1.815659
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{\text{Mott}}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-6.382	↗	0	↗	6.533	↗	114.983	↗	115.410
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-16.2545	↘	-16.2649	↗	-16.2545	↗	-13.7539	↗	-13.7362

In the degenerate Sn- $X(x)$ – alloy, for $T=106.71287$ K, one gets:

$N(10^{22}\text{cm}^{-3})$	↘	2.35291		2.3148734		2.2785		1.8865984		1.88548
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{\text{Mott}}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-6.545	↗	0	↗	6.714	↗	117.912	↗	118.349
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-16.6685	↘	-16.6792	↗	-16.6685	↗	-14.1043	↗	-14.0861

In the $Y(x) \equiv \text{CdTe}_{1-x}\text{Se}_x$ – alloy, for a given T and with decreasing N , the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T : (i) for $\xi_n \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{\text{min.}} (\approx -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{\text{max.}} = 1$, (ii) for $\xi_n = 1$, those of S , ZT , $(ZT)_{\text{Mott}}$, $VC1$, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $-1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$ respectively, and (iii) for $\xi_n \approx 1.8138$, $(ZT)_{\text{Mott}} = 1$.

For $x=0$,

In the degenerate P- $Y(x)$ – alloy, for $T= 29.1832614$ K, one gets:

$N(10^{27}\text{cm}^{-3})$	↘	1.126855		1.1086356		1.091215		0.90352685		0.902991
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320
ZT		0.999	↗	1	↘	0.999	↘	0.715	↘	0.713
$(ZT)_{\text{Mott}}$	↗	0.931		1		1.074		3.290		3.306
$VC1(10^{-4}\frac{V}{K})$		-0.061	↗	0	↗	0.063	↗	1.105	↗	1.109
$VC2(10^{-4}\frac{V}{K})$		-1.790	↗	0	↗	1.836	↗	32.246	↗	32.366
$T_s(10^{-4}\frac{V}{K})$		-0.092	↗	0	↗	0.094	↗	1.657	↗	1.663
Pt ($10^{-3}V$)		-4.5584	↘	-4.5613	↗	-4.5584	↗	-3.8571	↗	-3.8522

In the degenerate As- $Y(x)$ – alloy, for $T= 34.278521$ K, one gets:

$N(10^{27}\text{cm}^{-3})$	↘	1.434499		1.4113061		1.38913		1.1502002		1.149517
ξ_n	↘	1.880		1.8138		1.750		1		0.998
$S(10^{-4}\frac{V}{K})$		-1.562	↘	-1.563	↗	-1.562	↗	-1.322	↗	-1.320

ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931 ↗	1	1.074 ↘	3.290 ↘	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.103 ↗	0 ↗	2.157 ↗	37.876 ↗	38.017
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-5.3543 ↘	-5.3577 ↗	-5.3543 ↗	-4.5306 ↗	-4.5248

In the degenerate Sb- Y(x) – alloy, for T= 38.239921 K, one gets:

$N(10^{27}cm^{-3})$ ↘	1.690219	1.6628902	1.63677	1.3552387	1.354434
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931 ↗	1	1.074 ↘	3.290 ↘	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.346 ↗	0 ↗	2.405 ↗	42.253 ↗	42.410
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-5.9731 ↘	-5.9769 ↗	-5.9731 ↗	-5.0542 ↗	-5.0477

In the degenerate Sn- Y(x) – alloy, for T=39.214066 K, one gets:

$N(10^{27}cm^{-3})$ ↘	1.755214	1.7268353	1.6997	1.407353	1.40652
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931 ↗	1	1.074 ↘	3.290 ↘	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.405 ↗	0 ↗	2.467 ↗	43.329 ↗	43.490
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-6.1252 ↘	-6.1291 ↗	-6.1252 ↗	-5.1829 ↗	-5.1763

For x=0.5,

In the degenerate P- Y(x) – alloy, for T=31.825855 K, one gets:

$N(10^{27}cm^{-3})$ ↘	1.43826	1.4150071	1.39278	1.1532162	1.152532
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931 ↗	1	1.074 ↘	3.290 ↘	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-1.952 ↗	0 ↗	2.002 ↗	35.166 ↗	35.296
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-4.9712 ↘	-4.9744 ↗	-4.9712 ↗	-4.2064 ↗	-4.2010

In the degenerate As- Y(x) – alloy, for T= 37.382499 K, one gets:

$N(10^{27}cm^{-3})$ ↘	1.83092	1.8013205	1.773015	1.468058	1.467186
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320

ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.293 ↗	0 ↗	2.352 ↗	41.305 ↗	41.459
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-5.8391 ↘	-5.8429 ↗	-5.8391 ↗	-4.9408 ↗	-4.9345

In the degenerate Sb- Y(x) – alloy, for T=**41.702611 K**, one gets:

$N(10^{27}cm^{-3})$ ↘	2.15731	2.12243	2.08908	1.729759	1.728732
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.558 ↗	0 ↗	2.624 ↗	46.079 ↗	46.250
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-6.5139 ↘	-6.5181 ↗	-6.5139 ↗	-5.5118 ↗	-5.5047

In the degenerate Sn- Y(x) – alloy, for T=**42.764966 K** one gets:

$N(10^{27}cm^{-3})$ ↘	2.24026	2.2040462	2.16943	1.79627539	1.795209
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.623 ↗	0 ↗	2.689 ↗	47.253 ↗	47.428
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-6.6799 ↘	-6.6841 ↗	-6.6799 ↗	-5.6522 ↗	-5.6450

For x=1,

In the degenerate P- Y(x) – alloy, for T=**34.523903 K**, one gets:

$N(10^{27}cm^{-3})$ ↘	1.80655	1.7773443	1.74942	1.4485176	1.447658
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.117 ↗	0 ↗	2.172 ↗	38.147 ↗	38.289
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-5.3926 ↘	-5.3961 ↗	-5.3926 ↗	-4.5630 ↗	-4.5572

In the degenerate As- Y(x) – alloy, for T=**40.551614 K**, one gets:

$N(10^{27}cm^{-3})$ ↘	2.29976	2.26258	2.227029	1.8439798	1.842885
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320

ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.487 ↗	0 ↗	2.551 ↗	44.807 ↗	44.974
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-6.3342 ↘	-6.3382 ↗	-6.3342 ↗	-5.3597 ↗	-5.3528

In the degenerate Sb- Y(x) – alloy, for T=**45.237963 K**, one gets:

$N(10^{27}cm^{-3})$ ↘	2.709725	2.665915	2.624025	2.1726937	2.171403
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.775 ↗	0 ↗	2.846 ↗	49.985 ↗	50.171
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-7.0662 ↘	-7.0707 ↗	-7.0662 ↗	-5.9791 ↗	-5.9714

In the degenerate Sn- Y(x) – alloy, for T=**46.390382 K**, one gets:

$N(10^{27}cm^{-3})$ ↘	2.813927	2.7684306	2.72493	2.256243	2.254903
ξ_n ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2 \left(10^{-4} \frac{V}{K}\right)$	-2.846 ↗	0 ↗	2.919 ↗	51.259 ↗	51.449
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-3}V$)	-7.2462 ↘	-7.2508 ↗	-7.2462 ↗	-6.1314 ↗	-6.1235

Table 6p:

In the $X(x) \equiv CdTe_{1-x}S_x$ -crystalline alloy, for a given T and with decreasing N, the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_p \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{min.} (\approx -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_p = 1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $-1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$, respectively, and (iii) for $\xi_p \approx 1.8138$, $(ZT)_{Mott} = 1$.

For x=0,

In the degenerate Ga- X(x) – alloy, for T=**266.80841 K**, one gets:

$N(10^{27}cm^{-3})$ ↘	7.89954	7.7718202	7.6497	6.333955	6.330192
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109

VC2 (10^{-2} V)	-0.164 ↗	0 ↗	0.168 ↗	2.948 ↗	2.959
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt (10^{-2} V)	-4.1675 ↘	-4.1702 ↗	-4.1675 ↗	-3.5264 ↗	-3.5219

In the degenerate Mg- X(x) – alloy, for T= **318.94516 K**, one gets:

N (10^{22}cm^{-3}) ↘	1.032468	1.015775	0.999814	0.82784633	0.8273546
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
VC1 ($10^{-4} \frac{V}{K}$)	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
VC2 (10^{-2} V)	-0.196 ↗	0 ↗	0.201 ↗	3.524 ↗	3.537
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt (10^{-2} V)	-4.9819 ↘	-4.9851 ↗	-4.9819 ↗	-4.2155 ↗	-4.2101

In the degenerate In- X(x) – alloy, for T=**325.20128 K**, one gets:

N (10^{22}cm^{-3}) ↘	1.062994	1.0458077	1.029375	0.85232272	0.8518164
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
VC1 ($10^{-4} \frac{V}{K}$)	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
VC2 (10^{-2} V)	-0.199 ↗	0 ↗	0.205 ↗	3.593 ↗	3.607
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt (10^{-2} V)	-5.0796 ↘	-5.0829 ↗	-5.0796 ↗	-4.2982 ↗	-4.2926

In the degenerate Cd- X(x) – alloy, for T=**327.32434 K**, one gets:

N (10^{22}cm^{-3}) ↘	1.073421	1.0560657	1.039471	0.86068285	0.8601716
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
VC1 ($10^{-4} \frac{V}{K}$)	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
VC2 (10^{-2} V)	-0.201 ↗	0 ↗	0.206 ↗	3.617 ↗	3.630
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt (10^{-2} V)	-5.1128 ↘	-5.1161 ↗	-5.1128 ↗	-4.3262 ↗	-4.3207

For x=0.5,

In the degenerate Ga- X(x) – alloy, for T=**208.836003 K**, one gets:

N (10^{22}cm^{-3}) ↘	3.72778	3.6675104	3.6098	2.9889839	2.98721
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
VC1 ($10^{-4} \frac{V}{K}$)	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
VC2 (10^{-2} V)	-0.128 ↗	0 ↗	0.128 ↗	2.307 ↗	2.316

$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-3.2620 ↘	-3.2641 ↗	-3.2620 ↗	-2.7602 ↗	-2.7566

In the degenerate Mg- $X(x)$ – alloy, for $T=249.6443$ K, one gets:

$N(10^{22}cm^{-2})$ ↘	4.8722	4.793427	4.71812	3.9065942	3.904273
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.153 ↗	0 ↗	0.157 ↗	2.758 ↗	2.769
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-3.8994 ↘	-3.9019 ↗	-3.8994 ↗	-3.2995 ↗	-3.2953

In the degenerate In- $X(x)$ – alloy, for $T=254.54122$ K, one gets:

$N(10^{22}cm^{-2})$ ↘	5.01625	4.9351512	4.8576	4.0220984	4.019709
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.156 ↗	0 ↗	0.160 ↗	2.812 ↗	2.823
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-3.9759 ↘	-3.9785 ↗	-3.9759 ↗	-3.3643 ↗	-3.3599

In the degenerate Cd- $X(x)$ – alloy, for $T=256.20298$ K, one gets:

$N(10^{22}cm^{-2})$ ↘	5.065456	4.9835584	4.8921	4.0615497	4.05198
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.157 ↗	0 ↗	0.161 ↗	2.831 ↗	2.841
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-4.0019 ↘	-4.0044 ↗	-4.0019 ↗	-3.3862 ↗	-3.3849

For $x=1$,

In the degenerate Ga- $Y(x)$ – alloy, for $T=149.59434$ K, one gets:

$N(10^{22}cm^{-2})$ ↘	1.348259	1.3264601	1.30562	1.0810516	1.08041
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mett}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.092 ↗	0 ↗	0.094 ↗	1.653 ↗	1.659

$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-2.3367 ↘	-2.3381 ↗	-2.3367 ↗	-1.9772 ↗	-1.9746

In the degenerate Mg- Y(x) – alloy, for T=**178.82641** K, one gets:

$N(10^{22}cm^{-2})$ ↘	1.76217	1.7336801	1.70644	1.41293177	1.412093
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.110 ↗	0 ↗	0.112 ↗	1.976 ↗	1.983
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-2.7933 ↘	-2.7950 ↗	-2.7933 ↗	-2.3635 ↗	-2.3605

In the degenerate In- Y(x) – alloy, for T=**182.3341** K, one gets:

$N(10^{22}cm^{-2})$ ↘	1.81427	1.7849387	1.7569	1.454707	1.453843
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.112 ↗	0 ↗	0.114 ↗	2.014 ↗	2.022
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-2.8480 ↘	-2.8500 ↗	-2.8480 ↗	-2.4099 ↗	-2.4068

In the degenerate Cd- Y(x) – alloy, for T=**183.52446** K, one gets:

$N(10^{22}cm^{-2})$ ↘	1.83206	1.8024466	1.77413	1.4689757	1.468104
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.112 ↗	0 ↗	0.115 ↗	2.028 ↗	2.035
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
Pt ($10^{-2}V$)	-2.8666 ↘	-2.8685 ↗	-2.8666 ↗	-2.4256 ↗	-2.4225

For x=1,

In the degenerate Ga- Y(x) – alloy, for T=**149.59434** K, one gets:

$N(10^{22}cm^{-2})$ ↘	1.348259	1.3264601	1.30562	1.0810516	1.08041
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.092 ↗	0 ↗	0.094 ↗	1.653 ↗	1.659

$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-2.3367 ↘	-2.3381 ↗	-2.3367 ↗	-1.9772 ↗	-1.9746

In the degenerate Mg- $Y(x)$ – alloy, for $T=178.82641$ K, one gets:

$N(10^{22}cm^{-3})$ ↘	1.76217	1.7336801	1.70644	1.41293177	1.412093
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.110 ↗	0 ↗	0.112 ↗	1.976 ↗	1.983
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-2.7933 ↘	-2.7950 ↗	-2.7933 ↗	-2.3635 ↗	-2.3605

In the degenerate In- $Y(x)$ – alloy, for $T=182.3341$ K, one gets:

$N(10^{22}cm^{-3})$ ↘	1.81427	1.7849387	1.7569	1.454707	1.453843
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.112 ↗	0 ↗	0.114 ↗	2.014 ↗	2.022
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-2.8480 ↘	-2.8500 ↗	-2.8480 ↗	-2.4099 ↗	-2.4068

In the degenerate Cd- $Y(x)$ – alloy, for $T=183.52446$ K, one gets:

$N(10^{22}cm^{-3})$ ↘	1.83206	1.8024466	1.77413	1.4689757	1.468104
ξ_p ↘	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562 ↘	-1.563 ↗	-1.562 ↗	-1.322 ↗	-1.320
ZT	0.999 ↗	1 ↘	0.999 ↘	0.715 ↘	0.713
$(ZT)_{Mott}$ ↗	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061 ↗	0 ↗	0.063 ↗	1.105 ↗	1.109
$VC2(10^{-2}V)$	-0.112 ↗	0 ↗	0.115 ↗	2.028 ↗	2.035
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092 ↗	0 ↗	0.094 ↗	1.657 ↗	1.663
$Pt (10^{-2}V)$	-2.8666 ↘	-2.8685 ↗	-2.8666 ↗	-2.4256 ↗	-2.4225

In the $Y(x) \equiv CdTe_{1-x}Se_x$ – alloy, for a given T and with decreasing N , the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T : (i) for $\xi_p \approx 1.8138$, while the numerical results of S present a same minimum $(S)_{min.} (\approx -1.563 \times 10^{-4} \frac{V}{K})$, those of ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_p = 1$, those of S , ZT , $(ZT)_{Mott}$, $VC1$, and T_s present the same results: $-1.322 \times 10^{-4} \frac{V}{K}$, 0.715, 3.290, $-1.105 \times 10^{-4} \frac{V}{K}$, and $1.657 \times 10^{-4} \frac{V}{K}$ respectively, and (iii) for $\xi_p \approx 1.8138$, $(ZT)_{Mott} = 1$.

For $x=0$,

In the degenerate Ga- Y(x) – alloy, for T=266.80841 K, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	7.89954	7.7718202	7.6497	6.333955	6.330192
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.164	0	0.168	2.948	2.959
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \nearrow$	-4.1675	-4.1702	-4.1675	-3.5264	-3.5219

In the degenerate Mg- Y(x) – alloy, for T= 318.94516 K, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	1.032468	1.015775	0.999814	0.82784633	0.8273546
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.196	0	0.201	3.524	3.537
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \nearrow$	-4.9819	-4.9851	-4.9819	-4.2155	-4.2101

In the degenerate In- Y(x) – alloy, for T=325.20128 K, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	1.062994	1.0458077	1.029375	0.85232272	0.8518164
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.199	0	0.205	3.593	3.607
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \nearrow$	-5.0796	-5.0829	-5.0796	-4.2982	-4.2926

In the degenerate Cd- Y(x) – alloy, for T=327.32434 K, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	1.073421	1.0560657	1.039471	0.86068285	0.8601716
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.201	0	0.206	3.617	3.630
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \nearrow$	-5.1128	-5.1161	-5.1128	-4.3262	-4.3207

For x=0.5,

In the degenerate Ga- Y(x) – alloy, for T=208.836008 K, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	3.72778	3.6675104	3.60988	2.9889839	2.987209
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.128	0	0.131	2.307	2.316
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \searrow$	-3.2620	-3.2641	-3.2620	-2.7602	-2.7566

In the degenerate Mg- Y(x) – alloy, for T=**249.64443 K**, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	4.8722	4.793427	4.71811	3.9065945	3.904274
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.153	0	0.157	2.758	2.769
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \searrow$	-3.8994	-3.9019	-3.8994	-3.2995	-3.2953

In the degenerate In- Y(x) – alloy, for T=**254.54122 K**, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	5.016253	4.9351512	4.857603	4.0220984	4.01971
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.156	0	0.160	2.812	2.822
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \searrow$	-3.9759	-3.9785	-3.9759	-3.3643	-3.3599

In the degenerate Cd- Y(x) – alloy, for T=**256.20298 K**, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	5.065455	4.9835584	4.90525	4.0615497	4.059137
$\xi_p \searrow$	1.880	1.8138	1.750	1	0.998
$S(10^{-4}\frac{V}{K}) \searrow$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett} \nearrow$	0.931	1	1.074	3.290	3.306
$VC1(10^{-4}\frac{V}{K}) \nearrow$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V) \nearrow$	-0.157	0	0.161	2.831	2.841
$T_s(10^{-4}\frac{V}{K}) \nearrow$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V) \searrow$	-4.0019	-4.0044	-4.0018	-3.3862	-3.3819

For x=1,

In the degenerate Ga- Y(x) – alloy, for T=**149.59434 K**, one gets:

$N(10^{22}\text{cm}^{-2}) \searrow$	1.348259	1.3264601	1.30562	1.0810516	1.08041
-------------------------------------	----------	------------------	---------	------------------	---------

ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V)$	-0.092	0	0.094	1.653	1.659
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V)$	-2.3367	-2.3381	-2.3367	-1.9772	-1.9746

In the degenerate Mg- Y(x) – alloy, for T=**178.82641** K, one gets:

$N(10^{22}cm^{-2})$	1.76217	1.7336801	1.70644	1.41293177	1.412093
ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V)$	-0.110	0	0.112	1.976	1.983
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V)$	-2.7933	-2.7950	-2.7933	-2.3635	-2.3605

In the degenerate In- Y(x) – alloy, for T=**182.3341** K, one gets:

$N(10^{22}cm^{-2})$	1.81427	1.7849387	1.7569	1.454707	1.453843
ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V)$	-0.112	0	0.114	2.014	2.022
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V)$	-2.8480	-2.8500	-2.8480	-2.4099	-2.4068

In the degenerate Cd- Y(x) – alloy, for T=**183.52446** K, one gets:

$N(10^{22}cm^{-2})$	1.83206	1.8024466	1.77413	1.4689757	1.468104
ξ_p	1.880	1.8138	1.750	1	0.998
$S \left(10^{-4} \frac{V}{K}\right)$	-1.562	-1.563	-1.562	-1.322	-1.320
ZT	0.999	1	0.999	0.715	0.713
$(ZT)_{Mett}$	0.931	1	1.074	3.290	3.306
$VC1 \left(10^{-4} \frac{V}{K}\right)$	-0.061	0	0.063	1.105	1.109
$VC2(10^{-2}V)$	-0.112	0	0.115	2.028	2.035
$T_s \left(10^{-4} \frac{V}{K}\right)$	-0.092	0	0.094	1.657	1.663
$Pt(10^{-2}V)$	-2.8666	-2.8685	-2.8666	-2.4256	-2.4225